

## INDUSTRIAL COMPONENT DATA

# 70155600 H-B 24 TGBH 29 ZW. HOOD LAPP H-B 24 TGBH 29 ZW. HOOD

Brand: LAPP | Manufacturer Part Number: 70155600



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | LAPP                               |
| MPN / Reference | 70155600                           |
| Catalog number  | H-B 24 TGBH 29 ZW. HOOD            |
| Category        | Housing for rectangular connectors |
| Minimum order   | 5 Pcs                              |
| Document ID     | EO-EEFBA5E9AB                      |
| Generated       | 2026-08-06                         |

## Product Overview

H-B 24 TGBH 29 ZW. HOOD  
EPIC® H-B 24 TGBH

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                         |
|--------------|-------------------------|
| Catalog path | LAPP > EPIC rectangular |
|--------------|-------------------------|

## Additional Product Information

The universal metal housing for rectangular connectors can not only be used in investment construction. It has 2 double levers and a direct cable entry.

Non-slip ridges for comfortable disconnecting

For connection with counterpart with integrated cover

Protection rating UL50E tested

Benefits

Ideal for many applications due to a wide range of housings and inserts

More interior space for wiring

Application range

Plant engineering

Light & sound technology

Plastics industry

Product features

Hood, high version

Dual levers  
Straight cable entry  
Versions with / without neck  
Classification ETIM 5  
ETIM 5.0 Class-ID: EC000437  
ETIM 5.0 Class-Description: Housing for industrial connectors  
Classification ETIM 6  
ETIM 6.0 Class-ID: EC000437  
ETIM 6.0 Class-Description: Housing for industrial connectors  
Material  
Housing: powder-coated aluminium alloy, grey  
Lever: zinc-plated steel  
Sealing: NBR  
Protection rating  
IP 65 (latched)  
NEMA 250, UL50E: 12, 4 (latched)  
VDE-tested  
Certified production control: VDE-REG. no.: B437  
UL-tested:  
UL File Number: E75770  
Temperature range  
-40°C to +100°C, short-term up to +125°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 70155600 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.