

INDUSTRIAL COMPONENT DATA

70250220 EPIC ULTRA H-B 24 TS QB 11-21 LAPP EPIC ULTRA H-B 24 TS QB 11-21 (1)

Brand: LAPP | Manufacturer Part Number: 70250220



Manufacturer	LAPP
MPN / Reference	70250220
Catalog number	EPIC ULTRA H-B 24 TS QB 11-21
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-F2B46E764D
Generated	2026-08-05

Product Overview

EPIC ULTRA H-B 24 TS QB 11-21 (1)

EPIC® ULTRA H-B 24 TS QB

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > EPIC rectangular

Additional Product Information

EPIC® Rectangular connector housing EMC protection, corrosion resistant, UL50E, Nema250

EMC protection

Corrosion-resistant

Made in Germany

Benefits

Optimum, low-resistance 360° screening

All-purpose due to high corrosion resistance and high environmental protection.

Space-saving due to compact dimensions

Faster than any other comparable system

High mechanical resistance

Application range

In EMC-sensitive environments

For fixed and flexible applications (e.g. machinery building, wind turbines)

Construction machinery

Electric motor manufacturing

Product features

Housings with the BRUSH addition come with BRUSH cable screen contacting

Pluggable with standard housings

Corrosion-resistant according to DIN EN 6988

Resistance to cyclic salt spray is tested according to IEC 68-2-52, severity level 2

Salt spray testing according to DIN EN ISO 9227, method NSS, period of test 480 hours

Classification ETIM 5

ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6

ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material

Housing: nickel-plated zinc die-casting

Lever and bolts: stainless steel

Sealing: NBR

Cable gland

Body: nickel-plated brass

Insert: PA

Seal: special elastomer

Protection rating

IP 65

NEMA 250, UL50E: 12 (latched)

Temperature range

-40°C to +100°C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 70250220 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.