

INDUSTRIAL COMPONENT DATA

70261130 ÖLFLEX PLUG H03VV-F 3G0,75/1500 BK LAPP

ÖLFLEX PLUG H03VV-F 3G0,75/1500 BK

Brand: LAPP | Manufacturer Part Number: 70261130



Manufacturer	LAPP
MPN / Reference	70261130
Catalog number	ÖLFLEX PLUG H03VV-F 3G0,75/1500 BK
Category	Power cord
Minimum order	1 Pcs
Document ID	EO-5A016E4476
Generated	2026-08-04

Product Overview

ÖLFLEX PLUG H03VV-F 3G0,75/1500 BK

ÖLFLEX® PLUG H03VV-F Net Connection Cable*

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > Spiral cables

Additional Product Information

Application range

Electrical devices

Product features

For additional information regarding international plugs, please refer to our cable configurator at www.lappkabel.de

Apart from the cable related application restrictions to be paid attention to according to the application standard EN 50565-2 for this PVC cable H03VV-F, the fact that brighter outer sheath colours deviating from black significantly reduce the UV resistance of the outer sheath and, thus, the outdoor usability of the entire, finished cable has to be respected, too

Product Make-up

1st end: Gated, right-angled earthing-type plug with double earthing contact

Other end: 30 mm dismantled, with protection sleeves for the ends of the conductor

Alternatively, on request: 1st end with moulded right-angled earthing-type plug with twin earthed contact, 2nd end with moulded, straight IEC coupling (see image)

Classification ETIM 5

ETIM 5.0 Class-ID: EC001576

ETIM 5.0 Class-Description: Power cord

Classification ETIM 6

ETIM 6.0 Class-ID: EC001576

ETIM 6.0 Class-Description: Power cord

Core identification code

HD 308/VDE 0293-308: 3-core with protective conductor

Conductor stranding

Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5

Nominal voltage

U0: 250 V AC

Test voltage

2000 V

Protective conductor

G = with GN-YE protective conductor

Temperature range

5°C to 60°C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 70261130 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.