

**INDUSTRIAL COMPONENT DATA**

# 70261153 ÖLFLEX PLUG H05VV-F 3G1,5/3000 WH LAPP

## ÖLFLEX PLUG H05VV-F 3G1,5/3000 WH

Brand: LAPP | Manufacturer Part Number: 70261153



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | LAPP                              |
| MPN / Reference | 70261153                          |
| Catalog number  | ÖLFLEX PLUG H05VV-F 3G1,5/3000 WH |
| Category        | Power cord                        |
| Minimum order   | 10 Pcs                            |
| Document ID     | EO-E957827BCA                     |
| Generated       | 2026-08-02                        |

### Product Overview

ÖLFLEX PLUG H05VV-F 3G1,5/3000 WH  
ÖLFLEX® PLUG H05VV-F Net Connection Cable\*

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                      |
|--------------|----------------------|
| Catalog path | LAPP > Spiral cables |
|--------------|----------------------|

### Additional Product Information

ÖLFLEX® PLUG H05VV-F Net connecting cable, PVC, 1-2,5mm², 1.end angular earthing-type plug with double earthed contact/2.end IEC coupling or dismantled

Other colours and designs are available upon request

Application range

Electrical devices

Product features

For additional information regarding international plugs, please refer to our cable configurator at [www.lappkabel.de](http://www.lappkabel.de)

Apart from the cable related application restrictions to be paid attention to according to the application standard EN 50565-2 for this PVC cable H05VV-F, the fact that brighter outer sheath colours deviating from black significantly reduce the UV resistance of the outer sheath and, thus, the outdoor usability of the entire, finished cable at direct sun irradiation has to be respected, too

Product Make-up

1st end: Gated, rectangular earthing-type plug with double earthing contact

2nd end: straight, 3-pin IEC coupling, moulded

Alternative to Insulating tapes and shrink tubings

Classification ETIM 5

ETIM 5.0 Class-ID: EC001576

ETIM 5.0 Class-Description: Power cord

Classification ETIM 6

ETIM 6.0 Class-ID: EC001576

ETIM 6.0 Class-Description: Power cord

Core identification code

According to VDE 0293-308 (table T9)

Conductor stranding

Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5

Nominal voltage

U0: 250 V AC

Test voltage

2000 V

Protective conductor

G = with GN-YE protective conductor

Temperature range

5°C to 60°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 70261153 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.