

INDUSTRIAL COMPONENT DATA

71222243 ÖLFLEX PLUG CEE 5G6 32A 5m LAPP ÖLFLEX PLUG CEE 5G6 32A 5m

Brand: LAPP | Manufacturer Part Number: 71222243



Manufacturer	LAPP
MPN / Reference	71222243
Catalog number	ÖLFLEX PLUG CEE 5G6 32A 5m
Category	Power cord
Minimum order	1 Pcs
Document ID	EO-A7E5BFD54F
Generated	2026-08-04

Product Overview

ÖLFLEX PLUG CEE 5G6 32A 5m

ÖLFLEX® PLUG CEE Connection/ Extension Cable without phase shifter*

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > Spiral cables

Additional Product Information

ÖLFLEX® PLUG CEE Connection/extension cable without phase shifter, H07RN-F, plug/coupling three-phase AC/5-pole CEE, extension or one end dismantled

Formerly: ÖLFLEX PLUG CEE (400 V) Connection / Extension Cable

Application range

For connections to any three-phase A.C. consumers

Machines and systems on building sites

According to EN 50565-2: Dry or damp rooms as well as outdoors

Product features

Also available with phase shifter (engine direction can be changed)

Other dimensions, lengths, connectors, designs and customised versions are available upon request

Norm references / Approvals

H07RN-F cable type approval according to EN 50525-2-21

Product Make-up

Mounted 5-pin CEE plug, 400 V, red, 6 o'clock in accordance with VDE 0623/EN 60309-2, splash-proof IP 44

80 mm stripped, with conductor end sleeves
from 10 mm²: 100 mm stripped, with conductor end sleeves
Mounted 5-pin CEE coupling, 400 V, red, 6 o'clock in accordance with VDE 0623/EN 60309-2, splash-proof IP 44
Classification ETIM 5
ETIM 5.0 Class-ID: EC001576
ETIM 5.0 Class-Description: Power cord
Classification ETIM 6
ETIM 6.0 Class-ID: EC001576
ETIM 6.0 Class-Description: Power cord
Core identification code
According to VDE 0293-308 (table T9)
Conductor stranding
Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5
Nominal voltage
U0/U = 200/346 to 240/415
Test voltage
2500 V
Temperature range
Flexible use: -25°C to +60°C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 71222243 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.