

INDUSTRIAL COMPONENT DATA

71222292 ÖLFLEX PLUG CEE 5G1,5 16A 10m LAPP ÖLFLEX PLUG CEE 5G1,5 16A 10m

Brand: LAPP | Manufacturer Part Number: 71222292



Manufacturer	LAPP
MPN / Reference	71222292
Catalog number	ÖLFLEX PLUG CEE 5G1,5 16A 10m
Category	Power cord
Minimum order	1 Pcs
Document ID	EO-E61709F3F7
Generated	2026-08-04

Product Overview

ÖLFLEX PLUG CEE 5G1,5 16A 10m

ÖLFLEX® PLUG CEE Connection/ Extension Cable without phase shifter*

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > Spiral cables

Additional Product Information

ÖLFLEX® PLUG CEE Connection/extension cable without phase shifter, H07RN-F, plug/coupling three-phase AC/5-pole CEE, extension or one end dismantled

Formerly: ÖLFLEX PLUG CEE (400 V) Connection / Extension Cable

Application range

For connections to any three-phase A.C. consumers

Machines and systems on building sites

According to EN 50565-2: Dry or damp rooms as well as outdoors

Product features

Also available with phase shifter (engine direction can be changed)

Other dimensions, lengths, connectors, designs and customised versions are available upon request

Norm references / Approvals

H07RN-F cable type approval according to EN 50525-2-21

Product Make-up

Mounted 5-pin CEE plug, 400 V, red, 6 o'clock in accordance with VDE 0623/EN 60309-2, splash-proof IP 44

80 mm stripped, with conductor end sleeves

from 10 mm²: 100 mm stripped, with conductor end sleeves

Mounted 5-pin CEE coupling, 400 V, red, 6 o'clock in accordance with VDE 0623/EN 60309-2, splash-proof IP 44

Classification ETIM 5

ETIM 5.0 Class-ID: EC001576

ETIM 5.0 Class-Description: Power cord

Classification ETIM 6

ETIM 6.0 Class-ID: EC001576

ETIM 6.0 Class-Description: Power cord

Core identification code

According to VDE 0293-308 (table T9)

Conductor stranding

Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5

Nominal voltage

U0/U = 200/346 to 240/415

Test voltage

2500 V

Temperature range

Flexible use: -25°C to +60°C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 71222292 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.