

INDUSTRIAL COMPONENT DATA

73220856 ÖLFLEX SPIRAL 540 P 3G1/600 SHOCKPLG LAPP

ÖLFLEX SPIRAL 540 P 3G1/600 SHOCKPLG

Brand: LAPP | Manufacturer Part Number: 73220856



Manufacturer	LAPP
MPN / Reference	73220856
Catalog number	ÖLFLEX SPIRAL 540 P 3G1/600 SHOCKPLG
Category	Power cord
Minimum order	1 Pcs
Document ID	EO-6A349C031A
Generated	2026-08-04

Product Overview

ÖLFLEX SPIRAL 540 P 3G1/600 SHOCKPLG
ÖLFLEX® SPIRAL 540 P with angular, isolated ground plug

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > Spiral cables

Additional Product Information

ÖLFLEX® SPIRAL 540 P with angular, isolated ground plug - PUR spiral cable with high restoring forces, halogen free and oil-resistant power and control cable

Robust

High restoring forces

Benefits

Extension lengths of up to 3.5 times the unextended spiral length, high recoiling forces

The signal colour of the outer sheath increases safety and visual perception

Increased durability under harsh conditions thanks to robust PUR outer sheath

Sheath is resistant to contact with many mineral oil-based lubricants, diluted acids, aqueous alkaline solutions and other chemical media

Wide temperature range for applications in harsh climatic environments

Application range

Mobile electrical devices and apparatus

Medical equipment

Product features

Good resistance of the outer sheath to cutting and abrasion

Outer sheath has high resistance to oil, low temperatures, microbes and hydrolysis

Flexible down to -30°C

16-A connector with protection rating IP 20

Norm references / Approvals

Plug: DIN VDE 620-1/standard sheet DIN 49441 R2

Product Make-up

Cable: ÖLFLEX® SPIRAL 540 P based on ÖLFLEX® 540 P

Strands of tinned-copper wires

Core insulation: TPE

Outer sheath made of special polyurethane

Length of straight ends: 1st end = 200 mm with moulded angular earthing-type plug, 2nd end = 600 mm with 30 mm stripping

Other solid lengths, end lengths and end forms available on request

2-pin, angular plug with twin earthed contact system, extruded

Classification ETIM 5

ETIM 5.0 Class-ID: EC000247

ETIM 5.0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 73220856 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.