

**INDUSTRIAL COMPONENT DATA**

# 79145400 H-B 24 SDRH-BO M32 ZW. BOX MOUNT BASE LAPP

## H-B 24 SDRH-BO M32 ZW. BOX MOUNT BASE

Brand: LAPP | Manufacturer Part Number: 79145400



|                 |                                       |
|-----------------|---------------------------------------|
| Manufacturer    | LAPP                                  |
| MPN / Reference | 79145400                              |
| Catalog number  | H-B 24 SDRH-BO M32 ZW. BOX MOUNT BASE |
| Category        | Housing for rectangular connectors    |
| Minimum order   | 5 Pcs                                 |
| Document ID     | EO-E1B101D847                         |
| Generated       | 2026-08-04                            |

### Product Overview

H-B 24 SDRH-BO M32 ZW. BOX MOUNT BASE  
EPIC® H-B 24 SDRH-BO

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                         |
|--------------|-------------------------|
| Catalog path | LAPP > EPIC rectangular |
|--------------|-------------------------|

### Additional Product Information

The universal high metal housing consists of pivots for a double lever and a cable entry and is suitable, for example, for use in the plastics industry.

More interior space for wiring

Metal lid with sturdy hinge

Protection rating UL50E tested

Benefits

Safe fixing with 4 screws

Casted neck for easy assembly of the cable gland

Application range

Plant engineering

Light & sound technology

Plastics industry

Product features

Surface-mount base, high version

Bolts for double lever  
1 cable entry  
Metal cover  
Classification ETIM 5  
ETIM 5.0 Class-ID: EC000437  
ETIM 5.0 Class-Description: Housing for industrial connectors  
Classification ETIM 6  
ETIM 6.0 Class-ID: EC000437  
ETIM 6.0 Class-Description: Housing for industrial connectors  
Material  
Housing: powder-coated aluminium alloy, grey  
Lever: zinc-plated steel  
Sealing: NBR  
Protection rating  
IP 65 (latched)  
IP 40 (cover closed)  
NEMA 250, UL50E: 12, 4 (latched)  
VDE-tested  
Certified production control: VDE-REG. no.: B437  
UL-tested:  
UL File Number: E75770  
Temperature range  
-40°C to +100°C, short-term up to +125°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 79145400 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.