

**INDUSTRIAL COMPONENT DATA**

# 79150600 H-B 24 TGH M32 N.GEW. HOOD LAPP H-B 24 TGH M32 N.GEW. HOOD

Brand: LAPP | Manufacturer Part Number: 79150600



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | LAPP                               |
| MPN / Reference | 79150600                           |
| Catalog number  | H-B 24 TGH M32 N.GEW. HOOD         |
| Category        | Housing for rectangular connectors |
| Minimum order   | 5 Pcs                              |
| Document ID     | EO-E09C3DD2B3                      |
| Generated       | 2026-08-06                         |

## Product Overview

H-B 24 TGH M32 N.GEW. HOOD

EPIC® H-B 24 TGH

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      LAPP > EPIC rectangular

## Additional Product Information

The robust high metal housing contains the pivots for a double lever, a direct cable entry and can be supplied with or without a neck.

Non-slip ridges for comfortable disconnecting

More interior space for wiring

Protection rating UL50E tested

Benefits

Ideal for many applications due to a wide range of housings and inserts

M40 housing extension on M50 with SKINTOP 53112083 possible (clamping range 27 - 35 mm)

Application range

Plant engineering

Light & sound technology

Plastics industry

Product features

Hood, high version

Bolts for double lever  
Straight cable entry  
Versions with / without neck  
Classification ETIM 5  
ETIM 5.0 Class-ID: EC000437  
ETIM 5.0 Class-Description: Housing for industrial connectors  
Classification ETIM 6  
ETIM 6.0 Class-ID: EC000437  
ETIM 6.0 Class-Description: Housing for industrial connectors  
Material  
Housing: powder-coated aluminium alloy, grey  
Lever: zinc-plated steel  
Sealing: NBR  
Protection rating  
IP 65 (latched)  
NEMA 250, UL50E: 12, 4 (latched)  
VDE-tested  
Certified production control: VDE-REG. no.: B437  
UL-tested:  
UL File Number: E75770  
Temperature range  
-40°C to +100°C, short-term up to +125°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 79150600 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.