

INDUSTRIAL COMPONENT DATA

003951 LEGRAND LIMITER OVERVOLTAGE

Brand: LEGRAND | Manufacturer Part Number: 003951



Manufacturer	LEGRAND
MPN / Reference	003951
Catalog number	003951
Category	Surge protection device for power supply systems
Minimum order	1 Pcs
Document ID	EO-4D1C27A134
Generated	2026-07-29

Product Overview

LIMITER OVERVOLTAGE

Self-protected SPD - for consumer unit - T2 - I_{max} 12 kA/pole - 1P+N left

Self-Protected Surge Limiter Type 2 - 2P

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > MOTOR CIRCUIT BREAKERS

Additional Product Information

Pack (number of units)1

Volume (dm³)0.369

Weight (g)159.00

Product characteristicsProtection for consumer units

For residential and small commercial installations

With plug-in modules and status indicators:Green: SPD operational

Red: plug-in module need to be replaced

T2 self protected SPDs - I_{max} 12 kA/pole

For installations with low risk level (in urban areas, underground power supplies, etc.)

In: 10 kA/pole - U_c: 275 V~

Earthing systems: TT, TNS

Cat. No. 0 039 51: SPD with Y connection (both incoming and outgoing terminals at the top of the SPD) providing better protection against overvoltages

1P+N and 3P+N: L-N and N-PE protection modes (common and differential modes), the N pole being protected by

encapsulated spark gaps. Also called 1+1 and 3+1.

Number of poles : 1P+N

Neutral position : Left

Integrated protection : Isc ? 6 kA

Number of modules : 2

General characteristics Class II (T2) low voltage SPDs with integrated protection SPDs with integrated protection against overload currents and short-circuit currents

SPDs compliant with EN/IEC 61643-11 standards

For 230/400 VA power networks (50/60 Hz)

ETIM for 003951 Earthing, lightning and surge protection (EC000941)

Feature Name

Feature Value

System configuration TN-C-S (EF009933)

Yes

Degree of protection (IP) (EF005474)

IP20

Nominal voltage AC (EF004220)

230 V

System configuration TN-S (EF009930)

No

Construction size (EF002566)

2 modular spacing

System configuration other (EF009932)

No

Mounting method (EF000003)

DIN rail (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 003951 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.