

INDUSTRIAL COMPONENT DATA

012010 LEGRAND FUSE CYLINDRICAL /00/10

Brand: LEGRAND | Manufacturer Part Number: 012010



Manufacturer	LEGRAND
MPN / Reference	012010
Catalog number	012010
Category	Cylindrical fuse
Minimum order	10 Pcs
Document ID	EO-3305034948
Generated	2026-07-29

Product Overview

FUSE CYLINDRICAL /00/10

HRC cartridge fuse - cylindrical A typeM 8.5 x 31.5 - 10 A - without indicator

Cylindrical fuse cartridge - aM - 8.5x32 - without indicator - 10A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND > ACCESSORIES CONTROL AND CONTROL PANELS
--------------	--

Additional Product Information

Pack (number of units)10

Volume (dm3)0.036

Weight (g)45.00

Product characteristicsCylindrical type aM (motor rated)

Conform to EN 60269-1, IEC 60269-1 and 2

8 x 32 (previously 8.5 x 31.5)

Without indicator

Rating : 10 Amps

Voltage ~ : 400 Volts

Rupture capacity : 20000 Amps

General characteristicsHRC cartridge fuses

ETIM for 012010 Circuit breakers and fuses (EC002704)

Feature Name

Feature Value

Utilization category according to IEC 60269 (EF002572)

aM (switchgear protection)

Model (EF000010)

Ceramic fuse

Type of fuse status indicator (EF004473)

Other

Voltage type (EF000187)

AC/DC

Size (EF000088)

8x32mm

Power loss at rated current (EF012389)

1.2 W

Rated current (EF000227)

10 A

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 012010 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.