

INDUSTRIAL COMPONENT DATA

020275 LEGRAND XL3 DOOR SLIM MET 900H

Brand: LEGRAND | Manufacturer Part Number: 020275



Manufacturer	LEGRAND
MPN / Reference	020275
Catalog number	020275
Category	Door/operating panel (switchgear cabinet)
Minimum order	1 Pcs
Document ID	EO-32CFE92D52
Generated	2026-08-01

Product Overview

XL3 DOOR SLIM MET 900H

Door flat metal XL3 160/400 - to-box and wardrobe alt. 900 mm

Fuse enclosure, 4x3xE18, HxWxD=250x187.5x150mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND > XL3 160-400 ENERGY DISTRIBUTION CABINETS
--------------	--

Additional Product Information

Product features

Doors - Supplied with grip ram interchangeable (to be ordered separately) - 2 points lock up and down by the height of the 900-Planar - Distance-top cubrebornas/metal door: 38 mm - crystal: 34 mm - case and lockers, height 900 mm - Not adapted to the Vistop ergonomic front handle - Metal General characteristics

XL3 400 doors and equipment

ETIM for 020275 Cabinets and enclosures (EC000747)

Feature Name

Feature Value

Height (EF000040)

575 mm

Model (EF000010)

Compartment door

Degree of protection (IP) (EF005474)

IP40

Version as glazed door (EF006966)

No

Material (EF002169)

Steel

Surface finishing (EF006569)

Lacquered

Depth (EF000049)

25 mm

Colour (EF000007)

Grey

Version as door for disconnecting switch interlocking (EF006967)

No

Width (EF000008)

900 mm

EMC-version (EF001062)

No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 020275 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.