

INDUSTRIAL COMPONENT DATA

022534 LEGRAND VISTOP SWITCH 125A 3P MF

Brand: LEGRAND | Manufacturer Part Number: 022534



Manufacturer	LEGRAND
MPN / Reference	022534
Catalog number	022534
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-48ADDB2E91
Generated	2026-08-02

Product Overview

VISTOP SWITCH 125A 3P MF

SWITCH VISTOP 125A 3P MF

Vistop 125A 3 Pole Switch Disconnecter with Front Handle

Vistop disconnect switch - 125A - 3P - front control - black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **LEGRAND > INDUSTRIAL CONTACTORS / SWITCHES**

Additional Product Information

Conform to BS EN 60947-3 Bureau Veritas approved Safety switches for on-load circuit breaking by visible isolation of the contacts Double break type load switching with self cleaning contacts by rapid make and break movements Fixing on rail 4 EN 60715 or screw fixing (only on rail for Vistop 63 A) 2 versions for mounting on faceplate: * left or right side handle, supplied with seal to maintain the IP protection of the enclosure (up to IP 55), screws, self adhesive drilling template, extension rod (30 to 170mm) for creating an external angle * direct front handle or external handle with Cat. No. 0227

32Version as main switch Yes

Version as maintenance-/service switch Yes

Version as safety switch No

Version as emergency stop installation No

Version as reversing switch No

Max. rated operation voltage Ue AC 690 V

Rated operating voltage 690-690 V

Rated permanent current Iu 125 A

Rated permanent current at AC-21, 400 V 125 A
Rated short-time withstand current I_{cw} 3.5 kA
Rated operation power at AC-23, 400 V 70 kW
Switching power at 400 V 70 kW
Conditioned rated short-circuit current I_q 12 kA
Number of poles 3
Number of auxiliary contacts as normally closed contact 0
Number of auxiliary contacts as normally open contact 0
Number of auxiliary contacts as change-over contact 0
Motor drive optional No
Motor drive integrated No
Voltage release optional No
Device construction Built-in device fixed built-in technique
Suitable for floor mounting No
Suitable for front mounting 4-hole Yes....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 022534 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.