

INDUSTRIAL COMPONENT DATA

022554 LEGRAND SWITCH VISTOP 160A 3P ML

Brand: LEGRAND | Manufacturer Part Number: 022554



Manufacturer	LEGRAND
MPN / Reference	022554
Catalog number	022554
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-074CC02757
Generated	2026-07-29

Product Overview

SWITCH VISTOP 160A 3P ML

Isolating switch Vistop - 160 A - 3P - side handle, black - 7.5 modules

Vistop disconnect switch - 160A - 3P - side control - black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > INDUSTRIAL CONTACTORS / SWITCHES

Additional Product Information

Pack (number of units)1

Volume (dm3)2.313

Weight (g)738.00

Product characteristics63 to 160 A

Possibility to add auxiliary contact Cat.No 0 227 07

160 A

Side handle

3P

Connection : Key 6 sides

No of 17.5 mm modules : 7.5

General characteristicsVistop™isolating switches - 32 to 160 ASafety switches for on-load circuit breaking by visible isolation of the contacts

Double break type load switching with self cleaning contacts by rapid make and break movements

Fixing on rail EN 60715 or screw fixing (only on rail for Vistop 63 A)

Padlockable handle in open position: 1 to 3 padlocks Cat.No 0 227 97

2 versions for mounting on faceplate:right side handle, supplied with seal to maintain the IP protection for the enclosures (up to IP 55), screws, self adhesive drilling template, extension rod (30 to 170 mm) for creating an external angle direct front handle or external (for Vistop 63 to 160 A)

ETIM for 022554 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as safety switch (EF006985)

No

Version as maintenance-/service switch (EF006986)

Yes

Number of auxiliary contacts as normally open contact (EF001376)

0

Max. rated operation voltage Ue AC (EF007355)

690 V

Version as main switch (EF006981)

Yes

Number of auxiliary contacts as change-over contact (EF003531)

0

Number of auxiliary contacts as normally closed contact (EF001377)

0

Interlockable (EF006281)

Yes

Rated short-time withstand current Icw (EF007050)

3.5 kA

Voltage release optional (EF007...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 022554 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.