

INDUSTRIAL COMPONENT DATA**028688 LEGRAND DMX3-I 4000 FIXED 3POLOS 4000 TO**

Brand: LEGRAND | Manufacturer Part Number: 028688



Manufacturer	LEGRAND
MPN / Reference	028688
Catalog number	028688
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-D241F6521D
Generated	2026-08-03

Product Overview

DMX3-I 4000 FIXED 3POLOS 4000 TO

Trip free switch DMX³-I 4000 - fixed version - 3P - 4000 ADMX³ -I 4000 load cutting disconnecter - fixed - size 2 - 3P - In 4000A**STRUCTURED PRODUCT DATA****Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **LEGRAND > OPEN FRAME AUTOMATION DMX3****Additional Product Information**

Pack (number of units)1

Volume (dm3)298.584

Weight (g)82 500.00

Product characteristicsFixed version

Supplied with:4 auxiliary contacts: NO/NC

flat rear terminals for connection with bars

door sealing

DMX³-I 4000

Frame 4000

3P

In : 4000 A

General characteristicsTrip free switches DMX³-I - from 1250 to 6300 AConform to IEC 60947-3

ETIM for 028688 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as safety switch (EF006985)

Yes

Version as maintenance-/service switch (EF006986)

Yes

Number of auxiliary contacts as normally open contact (EF001376)

4

Max. rated operation voltage U_e AC (EF007355)

690 V

Version as main switch (EF006981)

Yes

Number of auxiliary contacts as change-over contact (EF003531)

4

Number of auxiliary contacts as normally closed contact (EF001377)

4

Interlockable (EF006281)

Yes

Rated short-time withstand current I_{cw} (EF007050)

85 kA

Voltage release optional (EF007491)

Yes

Device construction (EF008240)

Built-in device fixed built-in technique

Number of poles (EF001391)

3

Type of electrical connection of main circuit (EF006819)

Screw connection

Version as emergency stop installation (EF006959)

Yes

Motor drive integrated (EF006697)

Yes

Version as reversing switch (EF009408)

No

Type of control element (EF006976)

Push button

Conditioned rated short-circuit current I_q (EF001444)

85 kA

Rated operation power at AC-23, 400 V (EF007027)

1600 kW

Rated permanent current I_u (EF001389)

4000 A

Suitable for front mounting 4-hole (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 028688 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.