

INDUSTRIAL COMPONENT DATA

028693 LEGRAND DMX3-I 2500 FIXED 4POLOS 1250 TO

Brand: LEGRAND | Manufacturer Part Number: 028693



Manufacturer	LEGRAND
MPN / Reference	028693
Catalog number	028693
Category	Switch disconnect
Minimum order	1 Pcs
Document ID	EO-AFFF994509
Generated	2026-07-29

Product Overview

DMX3-I 2500 FIXED 4POLOS 1250 TO

Trip free switch DMX³-I 2500 - fixed version - 4P - 1250 ADMX³ -I 2500 Load Cutting Disconnect - Fixed - Size 1 - 4P - In 1250A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > OPEN FRAME AUTOMATION DMX3

Additional Product Information

Pack (number of units)1

Volume (dm3)192.421

Weight (g)61 900.00

Product characteristicsFixed version

Supplied with:4 auxiliary contacts: NO/NC

flat rear terminals for connection with bars

door sealing

DMX³-I 2500

Frame 2500

4P

In : 1250 A

General characteristicsTrip free switches DMX³-I - from 1250 to 6300 AConform to IEC 60947-3

ETIM for 028693 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as safety switch (EF006985)

Yes

Version as maintenance-/service switch (EF006986)

Yes

Number of auxiliary contacts as normally open contact (EF001376)

4

Max. rated operation voltage Ue AC (EF007355)

690 V

Version as main switch (EF006981)

Yes

Number of auxiliary contacts as change-over contact (EF003531)

4

Number of auxiliary contacts as normally closed contact (EF001377)

4

Interlockable (EF006281)

Yes

Rated short-time withstand current Icw (EF007050)

65 kA

Voltage release optional (EF007491)

Yes

Device construction (EF008240)

Built-in device fixed built-in technique

Number of poles (EF001391)

4

Type of electrical connection of main circuit (EF006819)

Screw connection

Version as emergency stop installation (EF006959)

Yes

Motor drive integrated (EF006697)

Yes

Version as reversing switch (EF009408)

No

Type of control element (EF006976)

Push button

Conditioned rated short-circuit current Iq (EF001444)

65 kA

Rated operation power at AC-23, 400 V (EF007027)

500 kW

Rated permanent current Iu (EF001389)

1250 A

Suitable for front mounting 4-hole (EF0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 028693 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.