

INDUSTRIAL COMPONENT DATA

028696 LEGRAND DMX3-I 2500 FIXED 4POLOS 2500

Brand: LEGRAND | Manufacturer Part Number: 028696



Manufacturer	LEGRAND
MPN / Reference	028696
Catalog number	028696
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-15E2BE7327
Generated	2026-08-02

Product Overview

DMX3-I 2500 FIXED 4POLOS 2500

Trip free switch DMX³-I 2500 - fixed version - 4P - 2500 A

DMX³ -I 2500 load cutting disconnecter - fixed - size 1 - 4P - In 2500A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > OPEN FRAME AUTOMATION DMX3

Additional Product Information

Pack (number of units)1

Volume (dm3)192.421

Weight (g)62 000.00

Product characteristicsFixed version

Supplied with:4 auxiliary contacts: NO/NC

flat rear terminals for connection with bars

door sealing

DMX³-I 2500

Frame 2500

4P

In : 2500 A

General characteristicsTrip free switches DMX³-I - from 1250 to 6300 AConform to IEC 60947-3

ETIM for 028696 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as safety switch (EF006985)

Yes

Version as maintenance-/service switch (EF006986)

Yes

Number of auxiliary contacts as normally open contact (EF001376)

4

Max. rated operation voltage Ue AC (EF007355)

690 V

Version as main switch (EF006981)

Yes

Number of auxiliary contacts as change-over contact (EF003531)

4

Number of auxiliary contacts as normally closed contact (EF001377)

4

Interlockable (EF006281)

Yes

Rated short-time withstand current Icw (EF007050)

65 kA

Voltage release optional (EF007491)

Yes

Device construction (EF008240)

Built-in device fixed built-in technique

Number of poles (EF001391)

4

Type of electrical connection of main circuit (EF006819)

Screw connection

Version as emergency stop installation (EF006959)

Yes

Motor drive integrated (EF006697)

Yes

Version as reversing switch (EF009408)

No

Type of control element (EF006976)

Push button

Conditioned rated short-circuit current Iq (EF001444)

65 kA

Rated operation power at AC-23, 400 V (EF007027)

1000 kW

Rated permanent current Iu (EF001389)

2500 A

Suitable for front mounting 4-hole (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 028696 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.