

INDUSTRIAL COMPONENT DATA

028698 LEGRAND DMX3-I 4000 FIXED 4POLOS 4000 TO

Brand: LEGRAND | Manufacturer Part Number: 028698



Manufacturer	LEGRAND
MPN / Reference	028698
Catalog number	028698
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-D7D7681F5F
Generated	2026-08-01

Product Overview

DMX3-I 4000 FIXED 4POLOS 4000 TO

Trip free switch DMX³-I 4000 - fixed version - 4P - 4000 ADMX³ -I 4000 load cutting disconnecter - fixed - size 2 - 4P - In 4000A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > OPEN FRAME AUTOMATION DMX3

Additional Product Information

Pack (number of units)1

Volume (dm3)298.584

Weight (g)93 000.00

Product characteristicsFixed version

Supplied with:4 auxiliary contacts: NO/NC

flat rear terminals for connection with bars

door sealing

DMX³-I 4000

Frame 4000

4P

In : 4000 A

General characteristicsTrip free switches DMX³-I - from 1250 to 6300 AConform to IEC 60947-3

ETIM for 028698 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as safety switch (EF006985)

Yes

Version as maintenance-/service switch (EF006986)

Yes

Number of auxiliary contacts as normally open contact (EF001376)

4

Max. rated operation voltage Ue AC (EF007355)

690 V

Version as main switch (EF006981)

Yes

Number of auxiliary contacts as change-over contact (EF003531)

4

Number of auxiliary contacts as normally closed contact (EF001377)

4

Interlockable (EF006281)

Yes

Rated short-time withstand current Icw (EF007050)

85 kA

Voltage release optional (EF007491)

Yes

Device construction (EF008240)

Built-in device fixed built-in technique

Number of poles (EF001391)

4

Type of electrical connection of main circuit (EF006819)

Screw connection

Version as emergency stop installation (EF006959)

Yes

Motor drive integrated (EF006697)

Yes

Version as reversing switch (EF009408)

No

Type of control element (EF006976)

Push button

Conditioned rated short-circuit current Iq (EF001444)

85 kA

Rated operation power at AC-23, 400 V (EF007027)

1600 kW

Rated permanent current Iu (EF001389)

4000 A

Suitable for front mounting 4-hole (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 028698 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.