

**INDUSTRIAL COMPONENT DATA**

# 028751 LEGRAND DMX3 2500 H EXTR 4POLOS 800 TO

Brand: LEGRAND | Manufacturer Part Number: 028751



|                 |                                                                   |
|-----------------|-------------------------------------------------------------------|
| Manufacturer    | LEGRAND                                                           |
| MPN / Reference | 028751                                                            |
| Catalog number  | 028751                                                            |
| Category        | Power circuit-breaker for trafo/generator/installation protection |
| Minimum order   | 1 Pcs                                                             |
| Document ID     | EO-0DBCDB52B1                                                     |
| Generated       | 2026-08-01                                                        |

## Product Overview

DMX3 2500 H EXTR 4POLOS 800 TO

Air circuit breaker DMX<sup>3</sup> 2500 Icu 65 kA - draw-out version - 4P - 800 A

Open frame circuit breaker DMX<sup>3</sup> 2500 - secc - 65kA - 4P - 800A

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      LEGRAND &gt; OPEN FRAME AUTOMATION DMX3

## Additional Product Information

Pack (number of units)1

Volume (dm3)192.421

Weight (g)85 500.00

Product characteristicsDraw-out version

Supplied with:4 auxiliary contacts: NO/NC

draw-out base and kit

flat rear terminals for connection with bars

door sealing

DMX<sup>3</sup> - H 2500

Breaking capacity Icu 65 kA (415 V~)

Frame 2500

4P

In : 800 A

General characteristicsAir circuit breakers DMX<sup>3</sup> 2500 and 4000 - from 800 to 4000 AAutomatic air circuit breakers must be

equipped with electronic protection unit, imperatively ordered together for factory assembly

Please ask for DMX<sup>3</sup> order form

Conform to IEC 60947-2

ETIM for 028751 Low-voltage industrial controls and switchgear (EC000228)

Feature Name

Feature Value

Degree of protection (IP) (EF005474)

IP30

Number of auxiliary contacts as change-over contact (EF003531)

4

Number of auxiliary contacts as normally closed contact (EF001377)

4

Adjustment range undelayed short-circuit release (EF007131)

1600 A

Integrated earth fault protection (EF007296)

Yes

With integrated under voltage release (EF001390)

Yes

Suitable for DIN rail (top hat rail) mounting (EF007250)

No

Device construction (EF008240)

Built-in device slide-in technique (withdrawable)

Number of poles (EF001391)

4

Overload release current setting (EF002336)

320 A

Motor drive integrated (EF006697)

Yes

Adjustment range short-term delayed short-circuit release (EF007129)

480 A

Type of control element (EF006976)

Push button

Rated short-circuit breaking capacity I<sub>cu</sub> at 400 V, 50 Hz (EF007048)

65 kA

Rated permanent current I<sub>u</sub>....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 028751 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.