

INDUSTRIAL COMPONENT DATA

028785 LEGRAND DMX3-I 2500 EXTR 3POLOS 2000 TO

Brand: LEGRAND | Manufacturer Part Number: 028785



Manufacturer	LEGRAND
MPN / Reference	028785
Catalog number	028785
Category	Switch disconnect
Minimum order	1 Pcs
Document ID	EO-59FA11E343
Generated	2026-08-03

Product Overview

DMX3-I 2500 EXTR 3POLOS 2000 TO

Trip free switch DMX³-I 2500 - draw-out version - 3P - 2000 ADMX³ -I 2500 Load Cutting Disconnect - 3P - In 2000A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > OPEN FRAME AUTOMATION DMX3

Additional Product Information

Pack (number of units)1

Volume (dm3)192.421

Weight (g)99 800.00

Product characteristicsDraw-out version

Supplied with:4 auxiliary contacts: NO/NC

draw-out base and kit

flat rear terminals for connection with bars

door sealing

DMX³-I 2500

Frame 2500

3P

In : 2000 A

General characteristicsTrip free switches DMX³-I - from 1250 to 6300 AConform to IEC 60947-3

ETIM for 028785 Low-voltage industrial controls and switchgear (EC000216)

Feature Name
Feature Value
Version as safety switch (EF006985)
Yes
Version as maintenance-/service switch (EF006986)
Yes
Number of auxiliary contacts as normally open contact (EF001376)
4
Max. rated operation voltage Ue AC (EF007355)
690 V
Version as main switch (EF006981)
Yes
Number of auxiliary contacts as change-over contact (EF003531)
4
Number of auxiliary contacts as normally closed contact (EF001377)
4
Interlockable (EF006281)
Yes
Rated short-time withstand current Icw (EF007050)
65 kA
Voltage release optional (EF007491)
Yes
Device construction (EF008240)
Built-in device slide-in technique (withdrawable)
Number of poles (EF001391)
3
Type of electrical connection of main circuit (EF006819)
Screw connection
Version as emergency stop installation (EF006959)
Yes
Motor drive integrated (EF006697)
Yes
Version as reversing switch (EF009408)
No
Type of control element (EF006976)
Push button
Conditioned rated short-circuit current Iq (EF001444)
65 kA
Rated operation power at AC-23, 400 V (EF007027)
800 kW
Rated permanent current Iu (EF001389)
2000 A
Suita...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 028785 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.