

## INDUSTRIAL COMPONENT DATA

## 028797 LEGRAND DMX3-I 4000 EXTR 4POLOS 3200

Brand: LEGRAND | Manufacturer Part Number: 028797



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | LEGRAND             |
| MPN / Reference | 028797              |
| Catalog number  | 028797              |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-ABB1F56B27       |
| Generated       | 2026-08-03          |

## Product Overview

DMX3-I 4000 EXTR 4POLOS 3200

Trip free switch DMX<sup>3</sup>-I 4000 - draw-out version - 4P - 3200 ADMX<sup>3</sup> -I 4000 Load Cutting Disconnecter - 4P - In 3200A

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path LEGRAND &gt; OPEN FRAME AUTOMATION DMX3

## Additional Product Information

Pack (number of units)1

Volume (dm3)298.584

Weight (g)162 700.00

Product characteristicsDraw-out version

Supplied with:4 auxiliary contacts: NO/NC

draw-out base and kit

flat rear terminals for connection with bars

door sealing

DMX<sup>3</sup>-I 4000

Frame 4000

4P

In : 3200 A

General characteristicsTrip free switches DMX<sup>3</sup>-I - from 1250 to 6300 AConform to IEC 60947-3

ETIM for 028797 Low-voltage industrial controls and switchgear (EC000216)

Feature Name  
Feature Value  
Version as safety switch (EF006985)  
Yes  
Version as maintenance-/service switch (EF006986)  
Yes  
Number of auxiliary contacts as normally open contact (EF001376)  
4  
Max. rated operation voltage Ue AC (EF007355)  
690 V  
Version as main switch (EF006981)  
Yes  
Number of auxiliary contacts as change-over contact (EF003531)  
4  
Number of auxiliary contacts as normally closed contact (EF001377)  
4  
Interlockable (EF006281)  
Yes  
Rated short-time withstand current Icw (EF007050)  
85 kA  
Voltage release optional (EF007491)  
Yes  
Device construction (EF008240)  
Built-in device slide-in technique (withdrawable)  
Number of poles (EF001391)  
4  
Type of electrical connection of main circuit (EF006819)  
Screw connection  
Version as emergency stop installation (EF006959)  
Yes  
Motor drive integrated (EF006697)  
Yes  
Version as reversing switch (EF009408)  
No  
Type of control element (EF006976)  
Push button  
Conditioned rated short-circuit current Iq (EF001444)  
85 kA  
Rated operation power at AC-23, 400 V (EF007027)  
1280 kW  
Rated permanent current Iu (EF001389)  
3200 A  
Sui...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 028797 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.