

**INDUSTRIAL COMPONENT DATA**

# 032752 LEGRAND LCS-CABLE C5E F/UTP DCA 305M. Sold in reels of 305 m. The unit price is per meter.

Brand: LEGRAND | Manufacturer Part Number: 032752



|                 |                              |
|-----------------|------------------------------|
| Manufacturer    | LEGRAND                      |
| MPN / Reference | 032752                       |
| Catalog number  | 032752                       |
| Category        | Data and communication cable |
| Minimum order   | 305 m.                       |
| Document ID     | EO-2E55C9713C                |
| Generated       | 2026-07-27                   |

## Product Overview

LCS-CABLE C5E F/UTP DCA 305M. Sold in reels of 305 m. The unit price is per meter.

Cable 4 pairs Cat. Cat5e FTP indoor LSZH 305m. Supplied in the box. Weight 12kg

4 pairs Cat.5e FTP cable LSZH cover 305m. Supplied in box. Weight 12kg

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      LEGRAND &gt; VDI CABLES

## Additional Product Information

**Product features**

Cables Cat. 5e Cable twisted 4-pair 100 ? Grey RAL 7035 colour Code EIA/TIA General characteristics

Legrand cabling system LCS3 cables and patch cords

ETIM for 032752 Cable (EC003249)

Feature Name

Feature Value

Protective sheath (EF001691)

None

Halogen free according to EN IEC 60754-2 (EF003792)

Yes

Reaction-to-fire according to EN 13501-6: Flaming droplets/particles (EF011579)

d2

Cable height approx. (EF003797)

5.9 mm

Reaction-to-fire according to EN 13501-6: Smoke production (EF011578)

s2

Reaction-to-fire according to EN 13501-6: Class (EF011577)

Dca

Weight (EF000167)

38

Cable width approx. (EF003796)

5.9 mm

Duplex (EF023003)

No

Cable type (EF000081)

F/UTP

Conductor surface (EF010804)

Bare

Oil resistant according to EN IEC 60811-404 (EF009770)

No

Number of stranding elements (EF001688)

4

With rip cord (EF017088)

No

Suitable for use as security alarm cable (EF017089)

No

Reaction-to-fire according to EN 13501-6: Acidity (EF011580)

a1

Min. permitted bending radius, stationary application/permanent installation (EF011803)

24 mm

Min. permitted bending radius, moving application/free movement (EF011802)

48 mm

Min. permitted bending radius, moving application with forced guidance (EF011801)

48 mm

Specification material outer sheath (EF011806)

Polyethylene (PE)

Specification core insulation (EF011805)

Polyethylene (PE)

Circuit integrity according to IEC 60331-23 (EF016619)

No

Category (EF001619)

5E

Approved type of underground installation (EF015176)

Other

Colour....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 032752 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.