


INDUSTRIAL COMPONENT DATA

032799 LEGRAND LCS-CABLE 6A F/FTP DCA 500M. Sold in reels of 500 m. The unit price is per meter.

Brand: LEGRAND | Manufacturer Part Number: 032799



Manufacturer	LEGRAND
MPN / Reference	032799
Catalog number	032799
Category	Data and communication cable
Minimum order	500 m.
Document ID	EO-E2601A9D35
Generated	2026-08-01

Product Overview

LCS-CABLE 6A F/FTP DCA 500M. Sold in reels of 500 m. The unit price is per meter.

Cable 4 pairs Cat. 6A F/FTP indoor LSZH 500 m. Supply in coil. Weight 25kg

4 pair Cat.6A F/FTP cable covered LSZH 500 m. Supply in coil. Weight 25kg

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND > VDI CABLES
--------------	----------------------

Additional Product Information

Product features

Cables Cat. 6A Cables 4 or 2x4 twisted pairs 100 ? Indoor LSZH : halogen-free Yellow RAL 1018 colour Code EIA/TIA

Conform to standards ISO/IEC 11801 edición 3.0 (2017), and EIA/TIA 568 C2-1 General characteristics

Legrand cabling system LCS3 cables and patch cords

ETIM for 032799 Cable (EC003249)

Feature Name

Feature Value

Protective sheath (EF001691)

None

Halogen free according to EN IEC 60754-2 (EF003792)

Yes

Reaction-to-fire according to EN 13501-6: Flaming droplets/particles (EF011579)

d2

Cable height approx. (EF003797)

7.5 mm

Reaction-to-fire according to EN 13501-6: Smoke production (EF011578)

s2

Reaction-to-fire according to EN 13501-6: Class (EF011577)

Dca

Weight (EF000167)

53

Cable width approx. (EF003796)

7.5 mm

Duplex (EF023003)

No

Cable type (EF000081)

F/FTP

Conductor surface (EF010804)

Bare

Oil resistant according to EN IEC 60811-404 (EF009770)

No

Number of stranding elements (EF001688)

4

With rip cord (EF017088)

No

Suitable for use as security alarm cable (EF017089)

No

Reaction-to-fire according to EN 13501-6: Acidity (EF011580)

a1

Min. permitted bending radius, stationary application/permanent installation (EF011803)

30 mm

Min. permitted bending radius, moving application/free movement (EF011802)

60 mm

Min. permitted bending radius, moving application with forced guidance (EF011801)

60 mm

Specification material outer sheath (EF011806)

Polyethylene (PE)

Specification core insulation (EF011805)

Polyethylene (PE)

Circuit integrity according to I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 032799 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.