

INDUSTRIAL COMPONENT DATA

032850 LEGRAND LCS-CABLE C5E F/UTP DCA 500M. Sold in reels of 500 m. The unit price is per meter.

Brand: LEGRAND | Manufacturer Part Number: 032850



Manufacturer	LEGRAND
MPN / Reference	032850
Catalog number	032850
Category	Data and communication cable
Minimum order	500 m.
Document ID	EO-5167D5886C
Generated	2026-08-01

Product Overview

LCS-CABLE C5E F/UTP DCA 500M. Sold in reels of 500 m. The unit price is per meter.

Lan cable - category 5e - F/UTP - 4 pairs - L. 500 m - LSZH sleeve

4 pair Cat.5e F/UTP cable LSZH cover 500m. Supply in coil. Weight 21kg

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND > VDI CABLES
--------------	----------------------

Additional Product Information

Pack (number of units)500

Volume (dm3)52.00

Weight (g)20 664.00

Product characteristicsCat. 5e cables for local networks

Performance 100 MHz

Cable with 4 twisted pairs, 100 ?

LSZH sheath: zero halogen

Grey RAL 7035

ANSI/TIA colour code

Compliant with ISO/IEC 11 801, EN 50173, ANSI/TIA 568 standards

Products conforming to the new CPR regulations

Euroclass Dca for LSZH cables, Euroclass Eca for PVC cables

F/UTP - 4 pairs

LSZH

Length 500 m

Supplied on reel

Weight 26 kg

General characteristics Legrand cabling system, LCS³ cat. 5e - cables and cords

ETIM for 032850 Cable (EC003249)

Feature Name

Feature Value

Protective sheath (EF001691)

None

Halogen free according to EN IEC 60754-2 (EF003792)

Yes

Reaction-to-fire according to EN 13501-6: Flaming droplets/particles (EF011579)

d2

Reaction-to-fire according to EN 13501-6: Smoke production (EF011578)

s2

Reaction-to-fire according to EN 13501-6: Class (EF011577)

Dca

Weight (EF000167)

38

Duplex (EF023003)

No

Cable type (EF000081)

F/UTP

Conductor surface (EF010804)

Bare

Number of stranding elements (EF001688)

4

Reaction-to-fire according to EN 13501-6: Acidity (EF011580)

a1

Min. permitted bending radius, stationary application/permanent installation (EF011803)

24 mm

Min. permitted bending radius, moving application with forced guidance (EF011801)

48 mm

Specification material outer sheath (EF011806)

Polyethylene (PE)

Specification core insulation (EF011805)

Polyethylene (PE)

Category (EF001619)

5E

Approved type of underground installation...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 032850 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.