


INDUSTRIAL COMPONENT DATA

032856 LEGRAND LCS-CABLE C6 F/UTP DCA 305M. Sold in reels of 305 m. The unit price is per meter.

Brand: LEGRAND | Manufacturer Part Number: 032856



Manufacturer	LEGRAND
MPN / Reference	032856
Catalog number	032856
Category	Data and communication cable
Minimum order	305 m.
Document ID	EO-701BD0735F
Generated	2026-08-03

Product Overview

LCS-CABLE C6 F/UTP DCA 305M. Sold in reels of 305 m. The unit price is per meter.

Cable 4 pairs Cat. 6 F/UTP indoor LSZH 305 m. Supply in coil. Weight 17 kg

4 pairs Cat.6 F/UTP cable LSZH 305 m cover. Supply in coil. Weight 17 kg

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND > VDI CABLES
--------------	----------------------

Additional Product Information

Product features

Cables Cat. 6 Wire 4 or 2 x 4 twisted pairs 100 ? Blue RAL 5015 colour Code EIA/TIA Conform to standards ISO/IEC 11801 edición 2, IN (2017) 50173-1 and EIA/TIA 568C General characteristics

Legrand cabling system LCS3 cables and patch cords

ETIM for 032856 Cable (EC003249)

Feature Name

Feature Value

Protective sheath (EF001691)

None

Halogen free according to EN IEC 60754-2 (EF003792)

Yes

Reaction-to-fire according to EN 13501-6: Flaming droplets/particles (EF011579)

d2

Reaction-to-fire according to EN 13501-6: Smoke production (EF011578)

s2

Reaction-to-fire according to EN 13501-6: Class (EF011577)

Dca

Weight (EF000167)

47

Duplex (EF023003)

No

Cable type (EF000081)

F/UTP

Conductor surface (EF010804)

Bare

Number of stranding elements (EF001688)

4

With rip cord (EF017088)

No

Suitable for use as security alarm cable (EF017089)

No

Reaction-to-fire according to EN 13501-6: Acidity (EF011580)

a1

Min. permitted bending radius, stationary application/permanent installation (EF011803)

28.5 mm

Min. permitted bending radius, moving application with forced guidance (EF011801)

57 mm

Specification material outer sheath (EF011806)

Polyethylene (PE)

Specification core insulation (EF011805)

Polyethylene (PE)

Category (EF001619)

6

Approved type of underground installation (EF015176)

Other

Colour outer sheath (EF001618)

Blue

Radial water blocking cable (EF011012)

Yes

Low smoke according to EN IEC 61034-2 (EF003799)

Yes

Longitudinal water blocking cable (EF011011)

No

Stranding....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 032856 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.