

INDUSTRIAL COMPONENT DATA

032882 LEGRAND LCS-CABLE C7 S/FTP B2CA 500M. Sold in reels of 500 m. The unit price is per meter.

Brand: LEGRAND | Manufacturer Part Number: 032882



Manufacturer	LEGRAND
MPN / Reference	032882
Catalog number	032882
Category	Data and communication cable
Minimum order	500 m.
Document ID	EO-67DFA85C27
Generated	2026-08-01

Product Overview

LCS-CABLE C7 S/FTP B2CA 500M. Sold in reels of 500 m. The unit price is per meter.

LCS-CABLE C7 S/FTP B2CA 500M

Cable for local networks LCS³ - category 7 - S/FTP - 4 pairs - 500 m

Category 7 S/FTP 4 pairs LSZH Euroclass B2ca 500 meters yellow cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > VDI CABLES

Additional Product Information

Pack (number of units)500

Volume (dm3)56.00

Weight (g)33 310.00

Product characteristicsCat. 7 cables for local networks

Performance 600 MHz

4 twisted pair cables, 100 ?

LSZH sheath: zero halogen. ANSI/TIA colour code

Compliant with ISO/IEC 11 801 and EN 50173standards

Products conforming to the new CPR regulation

S/FTP - 4 pairs

Length 500 m

Supplied on reel

Weight 45 kg

Euroclass B2 ca

LSZH :

Yellow :

General characteristics Legrand cabling system, LCS³ cat. 6A and category 7 - cables and cords

ETIM for 032882 Cable (EC003249)

Feature Name

Feature Value

Protective sheath (EF001691)

None

Halogen free according to EN IEC 60754-2 (EF003792)

Yes

Reaction-to-fire according to EN 13501-6: Flaming droplets/particles (EF011579)

d1

Cable height approx. (EF003797)

7.7 mm

Reaction-to-fire according to EN 13501-6: Smoke production (EF011578)

s1

Reaction-to-fire according to EN 13501-6: Class (EF011577)

B2ca

Weight (EF000167)

62

Cable width approx. (EF003796)

7.7 mm

Duplex (EF023003)

No

Cable type (EF000081)

S/FTP

Conductor surface (EF010804)

Bare

Oil resistant according to EN IEC 60811-404 (EF009770)

No

Number of stranding elements (EF001688)

4

With rip cord (EF017088)

No

Suitable for use as security alarm cable (EF017089)

No

Reaction-to-fire according to EN 13501-6: Acidity (EF011580)

a1

Min. permitted bending radius, stationary application/permanent installation (EF011803)

31 mm

Min. permitted bending radius, moving application/free movement (EF011802)

62 mm

Min. permitted bending rad...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 032882 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.