


INDUSTRIAL COMPONENT DATA

037153 LEGRAND B. VIKING3 EQUIP 1U P5 2,5MM2

Brand: LEGRAND | Manufacturer Part Number: 037153



Manufacturer	LEGRAND
MPN / Reference	037153
Catalog number	037153
Category	Feed-through terminal block
Minimum order	20 Pcs
Document ID	EO-66532E00D4
Generated	2026-07-28

Product Overview

B. VIKING3 EQUIP 1U P5 2,5MM2

Terminal block viking 3 - screw - function block - 1 connect - modular - pitch 5

Viking 3 terminal block with screw - 2.5² - 5 step

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > VIKING TERMINALS

Additional Product Information

Pack (number of units)20

Volume (dm3)0.558

Weight (g)238.00

Product characteristicsFunction blocks

1 connection - modular

Component connected with screws

Colour : Grey

Nominal cross-section : 2.5 mm²

Capacity - Rigid wire : 0.25 to 4 mm²

Capacity - Flexible wire with or without ferrules : 0.25 to 2.5 mm²

Pitch : 5 mm

General characteristicsViking™ 3 terminal blocks with screw connection - for copper cablesUsed to make the electrical connection between 2 flexible copper wires with or without ferrules or 2 rigid copper wires

2 areas for automatic insertion bridging combs up to 8 pitch (upper level only for multi-level blocks)

For rails depth 15 mm, EN 60715 depth 7.5 mm and 15 mm

ETIM for 037153 Terminal blocks (EC000897)

Feature Name

Feature Value

Number of clamp positions per level (EF002660)

2

Connectable conductor cross section solid-core (EF007337)

0.25 mm²

Internally connected stages (EF002661)

No

Height (EF000040)

46.5 mm

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.25 mm²

Inflammability class of insulation material according to UL94 (EF002521)

V2

Material insulation body (EF007543)

Thermoplastic

Mounting method (EF000003)

DIN rail (top hat rail) 35 mm

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.25 mm²

Explosion-tested version 'Ex e' (EF008498)

No

Connectable conductor cross section multi-wired (EF007343)

0.25 mm²

Operating temperature (EF002393)

-5 °C

Closing plate required (EF002525)

Yes

D...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 037153 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.