


INDUSTRIAL COMPONENT DATA

037156 LEGRAND BOR. VIKING3 2 LED FLOOR STEP 6

Brand: LEGRAND | Manufacturer Part Number: 037156



Manufacturer	LEGRAND
MPN / Reference	037156
Catalog number	037156
Category	Feed-through terminal block
Minimum order	60 Pcs
Document ID	EO-673FC40EF5
Generated	2026-08-02

Product Overview

BOR. VIKING3 2 LED FLOOR STEP 6

Terminal block viking 3 - screw- function bloc - 1 connect on 2 levels -with LED

Viking 3 terminal block with screw - 4² - 6 step

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > VIKING TERMINALS

Additional Product Information

Pack (number of units)60

Volume (dm3)2.094

Weight (g)1 085.00

Product characteristicsFunction blocks

2 connections on 2 levels - with LED

Voltage presence indicator (12/24V= and ~)

Colour : Grey

Nominal cross-section : 4 mm²

Capacity - Rigid wire : 0.25 to 6 mm²

Capacity - Flexible wire with or without ferrules : 0.25 to 4 mm²

Pitch : 6 mm

General characteristicsViking™ 3 terminal blocks with screw connection - for copper cablesUsed to make the electrical connection between 2 flexible copper wires with or without ferrules or 2 rigid copper wires

2 areas for automatic insertion bridging combs up to 8 pitch (upper level only for multi-level blocks)

For rails depth 15 mm, EN 60715 depth 7.5 mm and 15 mm

ETIM for 037156 Terminal blocks (EC000897)

Feature Name

Feature Value

Number of clamp positions per level (EF002660)

2

Connectable conductor cross section solid-core (EF007337)

0.25 mm²

Internally connected stages (EF002661)

Yes

Height (EF000040)

62.5 mm

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.25 mm²

Inflammability class of insulation material according to UL94 (EF002521)

V2

Material insulation body (EF007543)

Thermoplastic

Mounting method (EF000003)

DIN rail (top hat rail) 35 mm

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.25 mm²

Explosion-tested version 'Ex e' (EF008498)

No

Connectable conductor cross section multi-wired (EF007343)

0.25 mm²

Operating temperature (EF002393)

-5 °C

Rated current I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 037156 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.