


**INDUSTRIAL COMPONENT DATA**

# 037169 LEGRAND BOR.VIKING3 2PISO OF/35 STEP 6

Brand: LEGRAND | Manufacturer Part Number: 037169



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | LEGRAND                     |
| MPN / Reference | 037169                      |
| Catalog number  | 037169                      |
| Category        | Feed-through terminal block |
| Minimum order   | 25 Pcs                      |
| Document ID     | EO-985A12F4F7               |
| Generated       | 2026-08-03                  |

## Product Overview

BOR.VIKING3 2PISO OF/35 STEP 6

Viking 3 Connection Terminal Block 4mm<sup>2</sup> Screw Connection 2 Entry 2 Exit 6mm Grey

Viking 3 terminal block with screw - 6<sup>2</sup> - 6 step

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      **LEGRAND > VIKING TERMINALS**

## Additional Product Information

All V2 polyamide UL94 960°C to IEC EN 60695-2-11 Compatible with either rigid (0.25mm<sup>2</sup> to 95mm<sup>2</sup>) or flexible (0.25mm<sup>2</sup> to 70mm<sup>2</sup>) copper cables Facility for 2 bridging combs Compatible with rails depth 15mm and rails EN 60715 depth 7.5mm and 15mm Range comprises only 2 block heights (2.5mm<sup>2</sup> to 10mm<sup>2</sup> and 16mm<sup>2</sup> to 70mm<sup>2</sup>) ensuring a neat installation Connection Grey for standard circuit Blue for neutral conductor Orange for circuit not broken by the master isolating device Red for special circuits (safety, protected, etc)Connectable conductor cross section fine-strand without cable end sleeve 0.25-6 mm<sup>2</sup>

Connectable conductor cross section fine-strand with cable end sleeve 0.25-4 mm<sup>2</sup>

Connectable conductor cross section solid-core 0.25-6 mm<sup>2</sup>

Connectable conductor cross section multi-wired 0.25-4 mm<sup>2</sup>

Rated current I<sub>n</sub> 32 A

Rated voltage 500 V

Type of electrical connection 1 Screw connection

Type of electrical connection 2 Screw connection

Number of levels 1

Number of clamp positions per level 4  
Mounting method DIN rail (top hat rail) 35 mm  
Material insulation body Thermoplastic  
Operating temperature -5-40 °C  
Width 6 mm  
Height 51.5 mm  
Depth 57 mm  
Explosion-tested version 'Ex e' Yes  
Closing plate required Yes  
Colour Grey  
Internally connected stages No  
Inflammability class of insulation material according to UL 94 V2  
ETIM for 037169 Terminal blocks (EC000897)  
Feature Name  
Feature Value  
Number of clamp positions per level (EF002660)  
4  
Connectable conductor cross section solid-core (EF007...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 037169 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.