


INDUSTRIAL COMPONENT DATA

037179 LEGRAND BORNA VIKING3 2UN SIMP 2 FLOOR

Brand: LEGRAND | Manufacturer Part Number: 037179



Manufacturer	LEGRAND
MPN / Reference	037179
Catalog number	037179
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-466A9FF6D4
Generated	2026-07-31

Product Overview

BORNA VIKING3 2UN SIMP 2 FLOOR

Viking 3 Protection Terminal Block 4mm² Screw Connection 2 Entry 2 Exit Metal Base 6mm Green/YellowViking 3 terminal block with screw - 4² - 6 step

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > VIKING TERMINALS

Additional Product Information

All V2 polyamide UL94 960°C to IEC EN 60695-2-11 Compatible with either rigid (0.25mm² to 95mm²) or flexible (0.25mm² to 70mm²) copper cables Facility for 2 bridging combs Compatible with rails depth 15mm and rails EN 60715 depth 7.5mm and 15mm Range comprises only 2 block heights (2.5mm² to 10mm² and 16mm² to 70mm²) ensuring a neat installation Protection 1 connection - 2 entries/2 exits - metal base Screwless fixing on rail Connectable conductor cross section fine-strand without cable end sleeve 0.25-6 mm²

Connectable conductor cross section fine-strand with cable end sleeve 0.25-4 mm²Connectable conductor cross section solid-core 0.25-6 mm²Connectable conductor cross section multi-wired 0.25-4 mm²

Rated voltage 500 V

Type of electrical connection 1 Screw connection

Type of electrical connection 2 Screw connection

Number of levels 1

Number of clamp positions per level 4

Mounting method DIN rail (top hat rail) 35 mm

Material insulation body Thermoplastic
Operating temperature -5-40 °C
Width 6 mm
Height 51.5 mm
Depth 57 mm
Explosion-tested version 'Ex e' Yes
Closing plate required Yes
Colour Green/yellow
Internally connected stages No
Inflammability class of insulation material according to UL 94 V2
ETIM for 037179 Terminal blocks (EC000897)
Feature Name
Feature Value
Number of clamp positions per level (EF002660)
4
Connectable conductor cross section solid-core (EF007337)
0.25 mm²
Internally connected stages (EF002661)
No
Height (EF000040)
51.5 mm
Connectable conductor cro...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 037179 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.