


## INDUSTRIAL COMPONENT DATA

## 037202 LEGRAND B. VIKING3 RES neut mice 1U Q8 6MM2

Brand: LEGRAND | Manufacturer Part Number: 037202



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | LEGRAND                     |
| MPN / Reference | 037202                      |
| Catalog number  | 037202                      |
| Category        | Feed-through terminal block |
| Minimum order   | 50 Pcs                      |
| Document ID     | EO-CFF91989A8               |
| Generated       | 2026-08-04                  |

## Product Overview

B. VIKING3 RES neut mice 1U Q8 6MM2

Viking 3 Connection Terminal Block 6mm<sup>2</sup> Spring Connection 2 Cable 1 Entry 1 Exit 8mm BlueViking 3 Terminal with Spring - 6<sup>2</sup> - 8 Step

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path LEGRAND &gt; VIKING TERMINALS

## Additional Product Information

Screwless connection system, stainless steel spring type Compatible with either 2 rigid copper cables or flexible cables (0.5mm<sup>2</sup> - 16mm<sup>2</sup>) with or without ferrules Direct tool-free insertion of a rigid cable. Direct tool-free insertion of a flexible cable with ferrule, up to 6mm width Facility for 2 bridging combs Compatible with rails 2 EN 60715 depth 7.5mm and 15mm Connection Grey for standard circuit Blue for neutral conductor Orange for circuit not broken by the master isolating device Built-in end cap Connectable conductor cross section fine-strand without cable end sleeve 0.5-6 mm<sup>2</sup>

Connectable conductor cross section fine-strand with cable end sleeve 0.5-6 mm<sup>2</sup>Connectable conductor cross section solid-core 0.5-6 mm<sup>2</sup>Connectable conductor cross section multi-wired 0.5-6 mm<sup>2</sup>Rated current I<sub>n</sub> 41 A

Rated voltage 800 V

Type of electrical connection 1 Spring clamp connection

Type of electrical connection 2 Spring clamp connection

Number of levels 1

Number of clamp positions per level 2

Mounting method DIN rail (top hat rail) 35 mm  
Material insulation body Thermoplastic  
Operating temperature -5-40 °C  
Width 8 mm  
Height 44 mm  
Depth 66.5 mm  
Explosion-tested version 'Ex e' Yes  
Closing plate required No  
Colour Blue  
Internally connected stages No  
Inflammability class of insulation material according to UL 94 V2  
ETIM for 037202 Terminal blocks (EC000897)  
Feature Name  
Feature Value  
Number of clamp positions per level (EF002660)  
2  
Connectable conductor cross section solid-core (EF007337...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 037202 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.