

## INDUSTRIAL COMPONENT DATA

## 037271 LEGRAND B. VIKING3 RES V/A TIER P6 4MM2

Brand: LEGRAND | Manufacturer Part Number: 037271



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | LEGRAND                     |
| MPN / Reference | 037271                      |
| Catalog number  | 037271                      |
| Category        | Feed-through terminal block |
| Minimum order   | 50 Pcs                      |
| Document ID     | EO-D04271CB09               |
| Generated       | 2026-08-01                  |

## Product Overview

B. VIKING3 RES V/A TIER P6 4MM2

Viking 3 Protection Terminal Block 4mm<sup>2</sup> Spring Connection 2 Cable 1 Entry 1 Exit Metal Base 6mm Green/Yellow  
Viking 3 Terminal Block with Spring - 4<sup>2</sup> - 6 Step

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path      LEGRAND &gt; VIKING TERMINALS

## Additional Product Information

Screwless connection system, stainless steel spring type Compatible with either 2 rigid copper cables or flexible cables (0.5mm<sup>2</sup> - 16mm<sup>2</sup>) with or without ferrules Direct tool-free insertion of a rigid cable. Direct tool-free insertion of a flexible cable with ferrule, up to 6mm width Facility for 2 bridging combs Compatible with rails 2 EN 60715 depth 7.5mm and 15mm Protection Metal base Screwless fixing on rail PEN from 10mm<sup>2</sup> Built-in end cap Connectable conductor cross section fine-strand without cable end sleeve 0.5-6 mm<sup>2</sup>

Connectable conductor cross section fine-strand with cable end sleeve 0.5-4 mm<sup>2</sup>

Connectable conductor cross section solid-core 0.5-6 mm<sup>2</sup>

Connectable conductor cross section multi-wired 0.5-4 mm<sup>2</sup>

Rated voltage 800 V

Type of electrical connection 1 Spring clamp connection

Type of electrical connection 2 Spring clamp connection

Number of levels 1

Number of clamp positions per level 2

Mounting method DIN rail (top hat rail) 35 mm

Material insulation body Thermoplastic  
Operating temperature -5-40 °C  
Width 6 mm  
Height 42 mm  
Depth 54 mm  
Explosion-tested version 'Ex e' Yes  
Closing plate required No  
Colour Green/yellow  
Internally connected stages No  
Inflammability class of insulation material according to UL 94 V2  
ETIM for 037271 Terminal blocks (EC000897)  
Feature Name  
Feature Value  
Number of clamp positions per level (EF002660)  
2  
Connectable conductor cross section solid-core (EF007337)  
0.5 mm<sup>2</sup>  
Internally connected stages (EF002661)  
No  
Height (EF000040)  
42 mm  
Con...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 037271 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.