


INDUSTRIAL COMPONENT DATA

039015 LEGRAND B. SPLICE PLET-PLET 150-95

Brand: LEGRAND | Manufacturer Part Number: 039015



Manufacturer	LEGRAND
MPN / Reference	039015
Catalog number	039015
Category	(Knife) disconnect terminal block
Minimum order	5 Pcs
Document ID	EO-7C15AB0EF5
Generated	2026-07-31

Product Overview

B. SPLICE PLET-PLET 150-95

Viking 3 Heavy Duty Terminal Block 300mm² Cable Lug to Cable Lug 55mm

Viking 3 Power Terminal - Connection - Step 55

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **LEGRAND > VIKING TERMINALS**

Additional Product Information

Heavy duty terminal blocks For copper and aluminium cables IK 04 Conform to IEC 60947-7-1, EN 60947-7-1 UL 1059 and 486 E - CSA 22-2 Fire resistant IEC 60695-2-11: 960°C (except cover) V2 according to UL 94 Bridging the gap between the enclosure and external cables Fixed using metal clip for rails 15mm depth and EN 60715, 15mm depth or on plate with screws Fitted with hinged covers with cut-outs Permits the use of CAB 3 markers Test via test plug _4 closed covers Blocks with identical width can be joined using a threaded rod Supports shunt with Cat. Nos. 0394 46/47 Connectable conductor cross section fine-strand without cable end sleeve 300-300 mm²

Rated current In 670 A

Rated voltage 1000 V

Type of electrical connection 1 Bolt connection

Type of electrical connection 2 Bolt connection

Number of levels 1

Number of clamp positions per level 1

Internally connected stages No

Mounting method DIN rail (top hat rail) 35 mm

Material insulation body Thermoplastic
Operating temperature -5-40 °C
Width 55 mm
Height 113.5 mm
Depth 337 mm
Closing plate required No
Colour Grey
Type of slitting Swivelling
With integrated test socket Yes
Inflammability class of insulation material according to UL 94 V2
ETIM for 039015 Terminal blocks (EC000902)
Feature Name
Feature Value
Number of clamp positions per level (EF002660)
1
Internally connected stages (EF002661)
No
Height (EF000040)
113.5 mm
Inflammability class of insulation material according to UL94 (EF002521)
V2
Material insulation body (EF00...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 039015 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.