

INDUSTRIAL COMPONENT DATA

039071 LEGRAND POWER BLOCK OF 35MM2

Brand: LEGRAND | Manufacturer Part Number: 039071



Manufacturer	LEGRAND
MPN / Reference	039071
Catalog number	039071
Category	(Knife) disconnect terminal block
Minimum order	5 Pcs
Document ID	EO-A42DA5117A
Generated	2026-07-29

Product Overview

POWER BLOCK OF 35MM2

Viking 3 Heavy Duty Terminal Block Symmetrical DIN Rail Mounting 35mm² Copper Bar/Cable Lug 26mm

Viking 3 power terminal - symmetrical rails - M8 - 26 pitch - L15mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > VIKING TERMINALS

Additional Product Information

Heavy duty terminal blocks For copper bars or cable lugs Conform to IEC EN 60947-7-1 Fire resistance: 960°C, IEC EN 60695-2-11 V2 according to UL94 Insulating material: polyamide -30°C to +100°C Bridging the gap between the enclosure and external cables Plastic foot For use with terminal marker sheets For symmetrical rails Fixed using metal clip on rails 15mm depth and EN 60715, 15mm depth Connectable conductor cross section fine-strand without cable end sleeve 35-35 mm²

Rated voltage 1000 V

Type of electrical connection 1 Bolt connection

Type of electrical connection 2 Bolt connection

Number of levels 1

Number of clamp positions per level 1

Internally connected stages No

Mounting method DIN rail (top hat rail) 35 mm

Material insulation body Thermoplastic

Operating temperature -5-40 °C

Width 26 mm
Height 56 mm
Depth 84 mm
Closing plate required No
Colour Grey
Inflammability class of insulation material according to UL 94 V2
ETIM for 039071 Terminal blocks (EC000902)
Feature Name
Feature Value
Number of clamp positions per level (EF002660)
1
Internally connected stages (EF002661)
No
Height (EF000040)
56 mm
Inflammability class of insulation material according to UL94 (EF002521)
V2
Material insulation body (EF007543)
Thermoplastic
Mounting method (EF000003)
DIN rail (top hat rail) 35 mm
Connectable conductor cross section fine-strand without cable end sleeve (EF007341)
35 mm²
Operating temperature (EF002393)
-5 °C
Closing plate required (EF002525)
No
Depth (EF000049)
84 mm
Type....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 039071 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.