


INDUSTRIAL COMPONENT DATA

042664 LEGRAND TRNSF.CNOMO 230/24-48 250VA

Brand: LEGRAND | Manufacturer Part Number: 042664



Manufacturer	LEGRAND
MPN / Reference	042664
Catalog number	042664
Category	One-phase control transformer
Minimum order	1 Pcs
Document ID	EO-4E83155D57
Generated	2026-08-03

Product Overview

TRNSF.CNOMO 230/24-48 250VA

Transformer CNOMO TDCE version I - prim 230/400 V/sec 24-48 V - 250 VA

CNOMO TDCE Transformer version I - prim 230/400V/sec 24 - 48V - 250VA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > ACCESSORIES CONTROL AND CONTROL PANELS

Additional Product Information

Product features

For control circuit - an electrostatic shield (Version II) or 2-electrostatic screens (Version I) Primary: 230-400 V $\pm$ 15 V
-Secondary: 24 V (Version II) or 24 to 48 V (Version I) - 48 V by coupling 2 x 24 V (Version I) Version I: - Power: 250 VA -
PIA cos phi = 0,5: 750 VA - Gauge-circuit breaker protection for the secondary Version I: 6 A - Number of circuits provided:
2 General characteristics

Transformers - CNOMO - TDCE versions I and II - Meet the standard CNOMO E-03 22 210G version January 2007 -
complies with the standards IEC en 61558-2-2, 2-4 to 2 x 115 V and IEC en 61558-2-6 24 V - secondary Protection version
II: circuit breaker circuit breaker curve C for 100 and 160 VA, D curve from 250 to 1600 VA - Protection circuits use:
intended location (except 100 VA) for assembly by the user of circuit breakers residual current protection single-pole +
neutral, curve C with auxiliary contact investor

ETIM for 042664 Low-voltage industrial controls and switchgear (EC002486)

Feature Name

Feature Value

Primary voltage 2 (EF006126)

230 V
Built as isolating transformer (EF007238)
No
Height (EF000040)
200 mm
Primary voltage 1 (EF006125)
215 V
Degree of protection (IP) (EF005474)
IP20
Primary voltage 4 (EF007410)
385 V
Primary voltage 5 (EF007411)
400 V
Built as safety transformer (EF007235)
Yes
Rated apparent power (EF008864)
250 VA
Primary voltage 6 (EF007412)
415 V
Primary voltage 3 (EF006127)
245 V
Secondary voltage 1 (EF007472)
24 V
Relative short circuit vo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 042664 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.