

INDUSTRIAL COMPONENT DATA

044262 LEGRAND TRANSFORMER 230-400V/115-230V 63VA

Brand: LEGRAND | Manufacturer Part Number: 044262



Manufacturer	LEGRAND
MPN / Reference	044262
Catalog number	044262
Category	One-phase control transformer
Minimum order	1 Pcs
Document ID	EO-074BEBCE6D
Generated	2026-07-29

Product Overview

TRANSFORMER 230-400V/115-230V 63VA

Legrand Safety Isolating Transformer Single Phase 230/400V 115/230V 63VA

Transformer control and signal mono terminals w/screw - 230 - 400/115 - 230V 63V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > ACCESSORIES CONTROL AND CONTROL PANELS

Additional Product Information

IP2x or xxB up to 400VA IP xxA above 400VA - IK 04 Conform to IEC/EN 61558-2-2 and 2-4 or 2-6 UL506 and CSA C22-2-No66 Products suitable for building into equipment conforming to EN 61131-2, EN 60204-1 and EN 60439-1 standards Insulated covers up to 1000VA provided Interference/disturbance filter included Screw fix to mounting plate or clip on to DIN rail up to 250VA Supplied with 0V/Earth connection link up to 1000VABuilt as safety transformer No Built as isolating transformer Yes Built as energy saving transformer No

Primary voltage 1 215-215 V
Primary voltage 2 230-230 V
Primary voltage 3 245-245 V
Primary voltage 4 385-385 V
Primary voltage 5 400-400 V
Primary voltage 6 415-415 V
Secondary voltage 1 115-115 V
Secondary voltage 2 230-230 V

Rated apparent power 63 VA
Type of insulation material according to IEC 85 B
Short-circuit-proof No
Relative short circuit voltage 9.22 %
Width 94 mm
Height 85 mm
Depth 113 mm
Degree of protection (IP) IP2X
Ring core No
Suitable for mounting on PCB No
Suitable for distribution board Yes
degree of impact strength (IK) IK04
Voltage type AC
Terminal marking indication Yes
Connection type Screwed terminal
ETIM for 044262 Low-voltage industrial controls and switchgear (EC002486)
Feature Name
Feature Value
Primary voltage 2 (EF006126)
230 V
Built as isolating transformer (EF007238)
Yes
Height (EF000040)
85 mm
Primary voltage 1 (EF006125)
215 V
Degree of protection (IP) (EF005474)
IP2X
Primary voltage 4 (EF007410)
385 V
Primary voltage 5 (EF00...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 044262 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.