

INDUSTRIAL COMPONENT DATA

048556 LEGRAND DALI 3-ZONE CORRIDOR SENSOR

Brand: LEGRAND | Manufacturer Part Number: 048556



Manufacturer	LEGRAND
MPN / Reference	048556
Catalog number	048556
Category	Movement sensor for bus system
Minimum order	1 Pcs
Document ID	EO-9EF2A3A548
Generated	2026-07-29

Product Overview

DALI 3-ZONE CORRIDOR SENSOR
DALI 3-zone Light Up Sensor for aisle
DALI 3 zone Light Up Hall Sensor

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND
--------------	---------

Additional Product Information

Flexible range of sensors for all types of applications
Adapts the lighting to the presence and brightness
Wireless master-slave function to expand the detection area by associating a slave detector to the detector connected to the luminaire
Possibility of combining a battery-free wireless switch (ref. 7 418 13L/43L/73L) and a connected power socket (ref. 7 418 11/41/71)
Allows to manage and control 3 different lighting zones depending on daylight (+ function Setting Up with the Close Up App)
KNX bus system No
KNX-RF bus system (radio frequency) No
Radio frequency bus system Yes
LON Bus System No
Powernet Bus System No
Other bus systems Zigbee
Bidirectional Radio Frequency Yes
Model Presence detector
Type of mounting Recessed mounted (plaster)
Suitable for ceiling mounting Yes

Material Plastic
Material quality Thermoplastic
Surface Finish Mate
Colour White
RAL number (similar) 9003
Transparent No
With bus connection No
Input Extensions Yes
Creep Protection/Field Monitoring No
Operation Mode Switch No
Animal Zone No
Stair Lighting Controller Yes
Adjustable response brightness Yes
Learn function for responsive brightness Yes
DALI-2 Certified Yes
Optimal mounting height 2.5 m
Side reach 3 m
Front Reach 24 m
Horizontal Sensing Angle (Min-Max) 0-360 °
Number of channels 64
Minimum duty cycle 15 seconds
Maximum duty cycle 59 min
Width 103 mm
Height 95.8 mm
Depth 103 mm
Diameter 103 mm
Installation Depth 52.8 mm
Mounting Diameter 68 mm
Impact resistance IK04
Protection Class (IP) IP20
Op...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 048556 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.