

INDUSTRIAL COMPONENT DATA**061831 LEGRAND NT65 240LUM 1H IP65 NP**

Brand: LEGRAND | Manufacturer Part Number: 061831



Manufacturer	LEGRAND
MPN / Reference	061831
Catalog number	061831
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-63AAAB2C8D
Generated	2026-07-29

Product Overview

NT65 - 240LUM 1H IP65 NP

Luminaire emergency NT65 - 240 lumens - 1h - IP65 - Non-permanent

NT65 Emergency Luminaire - 240 lumens - 1h - IP65 - NP

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **LEGRAND > WATERTIGHT EMERGENCIES****Additional Product Information**

Product features

Luminaire, emergency standard - Non-permanent (NP) - 240 lumens - Autonomy 1 hour - IP65 - Lamp TL8W -

Battery-Ni-Cd - The test of maintenance is carried out manually General characteristics

NT65 - Luminaires for emergency watertight - Made according to the standards UNE-EN 60598-2-22 and UNE 20392 -

Luminaires non-permanent and multi - IP 65 - IK 07 - Power supply: 230 V $\pm$ 10 % - 50/60 Hz. Class I - 2 Leds greenwitness of load - Connection terminals large screw capacity for 2 cables of 2,5mm², both for food as the remote control. -

Terminals for remote operation to set at rest - the Protection of the network using the electronic device - automatic Material

of bse in sheet metal stamping - 2 entries for cable Ø 20 mm - Supplied with plug and cable gland - Installation in surface

ETIM for 061831 Luminaires (EC001957)

Feature Name

Feature Value

Conductor cross section (EF000085)

2.5 mm²

With remote control (EF000483)

No

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

No

Lamp type (EF002423)

Fluorescent lamp

Mounting method (EF000003)

Wall surface mounted

Connection type (EF000124)

Screw connection

Material cover (EF004284)

Plastic structured

With remote switch connection (EF007947)

No

Max. system power (EF009347)

240 W

Colour temperature (EF009346)

4000 K

Rated luminous flux according to IEC 62722-2-1 (EF009349)

240 lm

Number of lighting heads (EF004258)

1

Nominal current (EF009345)

1040 mA

Impact strength (EF004293)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 061831 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.