

INDUSTRIAL COMPONENT DATA

062425 LEGRAND HUBLOT KORO 100W WHITE

Brand: LEGRAND | Manufacturer Part Number: 062425



Manufacturer	LEGRAND
MPN / Reference	062425
Catalog number	062425
Category	HUBLOTS
Minimum order	5 units
Document ID	EO-8160962A34
Generated	2026-08-01

Product Overview

062425 LEGRAND HUBLOT KORO 100W WHITE

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Suitable for ceiling mounting (EF021180)	Yes
Lamp type (EF002423)	Incandescent lamp
With control gear (EF007556)	No
Suitable for surface mounting (EF007793)	Yes
Compatible with Apple HomeKit (EF014925)	No
Material cover (EF004284)	Plastic opal
Compatible with Amazon Alexa (EF014927)	No
Light distribution (EF004283)	Asymmetric
Compatible with Google Assistant (EF014926)	No
Light outlet (EF004282)	Direct
With light sensor (EF001203)	No
Max. system power (EF009347)	70 W
Colour temperature (EF009346)	2700 K
Nominal current (EF009345)	304 mA
Impact strength (EF004293)	IK08
Dimming DSI (EF012188)	No
Protection class according to IEC 61140 (EF000004)	II

CONTINUED

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Height/depth (EF001456)	118 mm
Width (EF000008)	261 mm
Built-in length (EF004265)	264 mm
Degree of protection (IP) (EF005474)	IP54
Voltage type (EF000187)	AC
Light distributor (EF012170)	Diffuser
With light source (EF005905)	Yes
With movement sensor (EF000197)	No
Suitable for emergency lighting (EF004275)	No
Nominal voltage (EF005127)	110 V
Dimming manufacturer's proprietary system (EF012159)	No
Suitable for light line configuration (EF004274)	No
IFTTT support available (EF011072)	No
Dimming phase cut-on (leading edge) (EF012162)	No
Dimming programmable (EF012163)	No
Dimming RF (EF012164)	No
Dimming Sine Wave Reduction (EF012165)	No
Dimming Touch and Dim (EF012166)	No
Dimming Zigbee (EF012167)	No
Dimming with push-button (EF012168)	No
Length (EF001438)	264 mm
Dimming mains voltage modulation (EF012160)	No
Dimming phase cut-off (trailing edge) (EF012161)	No
Covering of the luminaire with thermally insulating material possible (EF006423)	No
Type of grid (EF000282)	None
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)	No
Colour rendering index CRI (EF000442)	90-100
With air slots (EF009372)	No
Suitable for lamp power (EF000280)	70 W
Dimming 0-10 V (EF012152)	No
Dimming 1-10 V (EF012153)	No
Dimming DALI (EF012154)	No

CONTINUED

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Dimming DMX (EF012155)	No
Dimming potentiometer (integrated) (EF012156)	No
Dimming LineSwitch (EF012158)	No
Suitable for suspended mounting (EF001265)	No
Suitable for number of light sources (EF006436)	1
Lamp holder (EF000048)	E27
Type of control gear (EF000381)	Not required
Housing material (EF001596)	Plastic
Suitable for workplace according to EN 12464-1 (EF007694)	No
Suitable for built-in mounting (EF006760)	No
Colour of light (EF009350)	White
Outer diameter (EF000015)	261 mm
Housing colour (EF000136)	White
Rated ambient temperature according to IEC 62722-2-1 (EF012090)	-10 °C
Beam angle (EF008157)	Extreme wide beam >80°
Suitable for wall mounting (EF000664)	Yes

Classification & Catalog Path

Catalog path	LEGRAND > HUBLOTS
--------------	-------------------

Additional Product Information

Pack (number of units)5

Volume (dm3)42.00

Weight (g)3 616.00

Product characteristicsIP 54 - IK 08 Plexo rectangular bulkhead lights - class II

Polycarbonate diffuser, mounted on hinge

Opening can be reversed Top/Base

Supplied with one Plexo end cap, not assembled

Through wiring or terminal connection (side or rear)

Lampholder mounted on reflector (swivel pull-out type)

Grey base self-extinguishing: 850 °C

For E27 - 55 W halogen, 17 W compact fluorescent or 8 W LED lamps

IP 54 - IK 08 - class II

Polycarbonate diffuser, mounted on hinge

Opening can be reversed right/left

Supplied with 1 Plexo end cap, not assembled

Through wiring or terminal connection (side or back)

Through wiring or terminal connection (side or back)

Self-extinguishing at 850 °C

White

E 27

For E27 - 70 W halogen, 20 W compact fluorescent or 12 W LED lamps

General characteristics IP 44/54/55 weatherproof bulkhead lights - For domestic, commercial areas and tough environments

ETIM for 062425 Luminaires (EC002892)

Feature Name

Feature Value

Suitable for ceiling mounting (EF021180)

Yes

Lamp type (EF002423)

Incandescent I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 062425 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.