

INDUSTRIAL COMPONENT DATA

**069522LA LEGRAND Ecodetector, 230 V, with neutral, 3 wires.
IP 55 IK 08. Infrared detection. Detection dista..**

Brand: LEGRAND | Manufacturer Part Number: 069522LA



Manufacturer	LEGRAND
MPN / Reference	069522LA
Catalog number	069522
Category	Movement sensor complete
Minimum order	1 Pcs
Document ID	EO-5D2D1B1F3A
Generated	2026-08-04

Product Overview

Ecodetector, 230 V, with neutral, 3 wires. IP 55 - IK 08. Infrared detection. Detection distance: 8 m. detection angle 120 °.
Adjustable delay time: 5 sec at 30min. Light level threshold: 5 to 1275 lux.

Ecodetector, 230 V, with neutral, 3 wires

Ecodetector - 230V - with neutral - 3 wires

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LEGRAND > AUTONOMOUS LIGHTING MANAGEMENT
--------------	--

Additional Product Information

Ecodetector from the Plexo range, designed in gray/white color. It has an infrared detection system (detection distance 8 m, detection angle 120°), brightness threshold regulation from 5 lux to 1275 lux, timing regulation from 5 s to 30min. Suitable for installation in boxes with a depth of 50mm. 230 VA, IP 55 - IK 08, standby consumption: 0.01 W. Ecodetector with neutral - 3 wires, it is installed instead of a simple switch and does not require additional wiring, power accepted by lamp type up to 250W. Up to 10 detectors can be installed in parallel. For LEDs and fluorescent lamps, if several detectors are installed in the same circuit, the minimum load increases. Model Motion Sensor

Motion sensor technology Passive Infrared

Constant light dimming No

Control de HVAC No

Forced connection No

Forced disconnection No

Animal Zone No

Creep Protection/Field Monitoring No
Background monitoring No
Networkable No
Scanning angle 120 °
Optimal mounting height 1.2 m
Stair Lighting Controller Yes
Bypass switch No
Side reach 4 /
Detection field presence max. 32 m²
Front Reach 8 m
Suitable for wireless streaming No
Remote control Yes
With remote control No
Adjustable response sensitivity Yes
Adjustable response brightness Yes
With signalling unit Yes
Learn function for responsive brightness No
Control function with control insert No
Type of mounting Surface mounted (plaster)
Suitable for ceiling mounting No
Suitable for wall mounting Yes
Connection Method Screw-on terminal
Material Plastic....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 069522LA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.