

INDUSTRIAL COMPONENT DATA

069548L LEGRAND PL-COMP I/O PULS EMERG 3A LLAV

Brand: LEGRAND | Manufacturer Part Number: 069548L



Manufacturer	LEGRAND
MPN / Reference	069548L
Catalog number	069548L
Category	Emergency stop complete
Minimum order	1 Pcs
Document ID	EO-89148C4BAC
Generated	2026-07-29

Product Overview

PL-COMP I/O PULS EMERG 3A LLAV

Plexo composable emergency button - unlock with reset key

Plexo Modular Emergency Push Button - with Reset Key

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND

Additional Product Information

Overview

This button allows an emergency power cut. Includes "emergency cut" labels. Composable product for surface or recessed installation. Contact NA+NC.

Product features

Plexo Composable Emergency Push Button - Grey/Yellow - To be installed with a frame for recessed installation or in a surface box.

IP55 - 3A - 250V - IK07

Emergency button with reset key - Contact NA+NC

Yellow lid - Red button

Supplied with "emergency stop" label in 4 languages

Recommendations / Restrictions

Removable keys in position 0

Supplied with a set of 2 RONIS keys n°455

description

PLEXO surface or recessed emergency push button with key unlocking RONIS N°455. Emergency cut 3A - 250V - Includes "emergency cut" labels in 4 languages - Yellow cap - Red button - NA + NC contact - Gray/yellow. Plexo - IP 55 watertight mechanisms - composable - emergency cut-off, beacon, blinds, thermostat. - Removable keys in position 0 - Supplied with a set of 2 keys. Highlights

Advantages in installation

Installation of the mechanism on the surface or recessed with box or frame

specifications

Unlock Type Decoupling by key

Number of Normally Closed Contacts 1

Number of contacts normally opened 1

Protection Class (IP) IP55

With light No

Hole diameter 22.5 mm

Auxiliary Circuit Connection Type Threaded connection

Width 70.5 mm

Height 70.5 mm

Depth 73 mm

Impact resistance IK07

Operating Temperature -10-40 °C

Storage temperature -25-60 °C

Type of voltage AC

Nominal Voltage 220-250 V

Terminal capacity 1.5-2.5 mm²

ETIM for....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 069548L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.