

INDUSTRIAL COMPONENT DATA

069559L LEGRAND PL-COMP BASE RJ45 CAT6A STP GR

Brand: LEGRAND | Manufacturer Part Number: 069559L



Manufacturer	LEGRAND
MPN / Reference	069559L
Catalog number	069559L
Category	Data communication connection box copper (twisted pair)
Minimum order	5 Pcs
Document ID	EO-86999F1794
Generated	2026-08-02

Product Overview

PL-COMP BASE RJ45 CAT6A STP GR
RJ45 Cat.6 STP Plexo Base - modular - Gray
RJ45 Cat.6 STP Plexo modular base - Gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **LEGRAND**

Additional Product Information

Overview

The RJ45 dock connects a device (PC, printer) to the local network (Internet box, switch). Cable distribution ensures a high-speed, secure, and reliable internet connection.

Product features

Base RJ45 Cat. 6 STP Plexo - modular - Grey
description

RJ45 Databases - Cat. 6 - STP - Modular - Plexus - Grey - Tool-free quick connect bases - IP55 (with closed cover) - IK08 -
For recessed or surface installation in frame or box.Highlights

Advantages in installation

Installation of the mechanism on the surface or recessed with box or frame
specifications

Surface mounting Yes

Flush mounting Yes

Duct Installation No

Ground-mounted/underground box No
Attachment Type Screw
Type of mounting Basic element with center cover plate, Surface-mounted/slotted
Connector Type 2x RJ45 8(8)
With sockets/couplings Yes
Suitable for the number of sockets/couplings 1
category 6A (IEC)
Colour Grey
RAL number 7046
Connection Method Insulation Displacement Connector
Shielded plugs Yes
Shielded housing No
Separate grounding connection No
With text box Yes
Separate cable strain relief No
Shielding Connection Mount Type none
Exit Address Straight
With dust protection Yes
With termination resistance No
Protection Class (IP) IP55
Mechanical Coding Yes
Color coding Yes
Device width 70.5 mm
Device height 70.5 mm
Device Depth 44.75 mm
Impact resistance IK08
Operating Temperature -5-35 °C
Storage temperature -25-60 °C
Display of markings on the connection terminals Yes
Halogen-free Yes
Antibacterial treatm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 069559L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.