

INDUSTRIAL COMPONENT DATA

069583L LEGRAND PL-COMP BEACON PILOT I/O

Brand: LEGRAND | Manufacturer Part Number: 069583L



Manufacturer	LEGRAND
MPN / Reference	069583L
Catalog number	069583L
Category	Information light signal for domestic switching devices
Minimum order	10 Pcs
Document ID	EO-CB6571D4C2
Generated	2026-08-01

Product Overview

PL-COMP BEACON PILOT I/O

Plexo modular gray/white beacon pilot - for E10 lamp - 230 V

Plexo modular beacon pilot for E10 lamp - 230V - Gray/White

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND

Additional Product Information

Overview

Plexo pilot that allows beacon lighting such as a corridor, a staircase... For installation requiring protection against water and dust.

Product features

Composable Plexo Signal Pilot - Grey/White

IP55 - IK08

2 power levels available (0.2W or 1W)

Screw terminal

Supports diffuser references 0 695 88L/89L/90L/91L

description

Modular PLEXO signaling light. Beaconing and signaling - IP 55 - IK 08 pilot - Mechanism that integrates the LEDs - 2

available power levels (0.2W or 1W) - Terminal with screws - Compatible with diffusers ref. 0 695 88L/89L/90L/91L -

Gray/White. Plexo - IP 55 watertight mechanisms - composable - emergency cut-off, beacon, blinds, thermostat.Highlights

Advantages in use

Signage

specifications

Type of mounting Other , Other

Lamp holder none

With light source Yes

Lamp Non-interchangeable LED

With flashing light No

With fixed symbol/printing No

With interchangeable symbol No

Can be used as a pushbutton No

Attachment Type Thread fastening

Material Plastic

Material quality Thermoplastic

Halogen-free Yes

Surface treatment No treatment

Surface Finish Mate

Colour Grey

RAL number (similar) 7040

Transparent No

Lamp color White

Suitable for protection grade (IP) IP55

Nominal Voltage 230 V

Lamp power max. 1 W

Device width 68.5 mm

Device height 68.5 mm

Device Depth 41.2 mm

Impact resistance IK07

Operating Temperature -10-40 °C

Storage temperature -25-60 °C

Type of voltage AC

frequency 50-60 Hz

Neutral Mandatory Yes

Display of markings on the connection terminals...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 069583L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.