

INDUSTRIAL COMPONENT DATA

076533 LEGRAND MO-BASE RJ45 C6 FTP ENROLL BL

Brand: LEGRAND | Manufacturer Part Number: 076533



Manufacturer	LEGRAND
MPN / Reference	076533
Catalog number	076533
Category	Data communication connection box copper (twisted pair)
Minimum order	1 Pcs
Document ID	EO-7729A06F66
Generated	2026-08-01

Product Overview

MO-BASE RJ45 C6 FTP ENROLL BL

RJ45 Mosaic Base. Cat.6 FTP. 4 modules. With 0.9m reel. White

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > RJ45 CONNECTORS

Additional Product Information

RJ45 Mosaic Cat.6 FTP socket with 0.9 m roll-up cable. 4 modules. The RJ45 Mosaic socket connects a device (PC, printer) to the local network (ISP router, switch). Cable distribution ensures a high-speed, secure, and reliable Internet connection. It is completed with a plate and support. Cat 6 : Data transmission rate of up to 1 GigaBit/s. This allows you to download a 1 GigaByte file in 8 seconds. Supports high-capacity PoE applications. Power over Ethernet passes electrical power along with data into twisted-pair Ethernet cabling. Equipped with a transparent protective cover that protects the connector, and an integrated retractable cable to easily plug in your device. Very suitable for downloading, streaming, or online gaming that requires low latency. Compatible with cables equipped with RJ11, RJ12 or RJ45 plugs. Tool-free connector with quick connection thanks to integrated crimping. The slot system allows for perfect and easy placement of several hooks. The support frames can be joined perfectly, making installation easier. It can be installed in a normal (simple) flush-mounted box, without the need for additional cuts in wall slots or wiring. They accept single AWG 22 to AWG 26 and AWG 26 multi-thread. Contacts with double color code with numbers 568 a and B. Conforms to ISO/IEC 11801 ed. 2.0, EN 50173-1 and ANSI/TIA 568 C2. White. Dimension 33.5x36x89.7mm. Breakdown voltage ≥ 1000 V. Contact resistance ≤ 20 m Ω . Insulation resistance ≥ 500 m Ω at 100V DC. Maximum number....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 076533 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.