

## INDUSTRIAL COMPONENT DATA

## 077532 LEGRAND MO-INTER DIF 16A 30MA 2M BL

Brand: LEGRAND | Manufacturer Part Number: 077532



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | LEGRAND                       |
| MPN / Reference | 077532                        |
| Catalog number  | 077532                        |
| Category        | Earth leakage circuit breaker |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-8BE715F393                 |
| Generated       | 2026-07-27                    |

## Product Overview

MO-INTER DIF 16A 30MA 2M BL

RCBO Mosaic - 1 pole - with N 230 V~ and test button - 16 A - 30 mA - 2 modules -white

Mosaic differential circuit breaker - 1P+N - 16A - 30mA- 2mod - White

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path LEGRAND &gt; MOSAIC, ARTEOR AND CELIANE MECHANISMS

## Additional Product Information

Pack (number of units)1

Volume (dm3)0.188

Weight (g)86.00

Product characteristicsProximity MCBs

Used for local protection of part of a circuit against overloads and short circuits

Used in addition to the main protection device

Due to its proximity to the user and its discrimination with the main protection device, the restart can be immediate  
2 modules

Single pole RCBOs + Neutral 230 V~

Provides additional protection of people (premises with conductive flooring, presence of water, etc.) against direct contact  
with live parts or earth leakages

White

16 A - 30 mA with test button

General characteristicsMosaic™ Programme mechanisms - voltage surge protector, replacement module, buzzers, bells,

blanking plates, cable outlets and proximity MCBs

ETIM for 077532 Circuit breakers and fuses (EC000905)

Feature Name

Feature Value

Frequency (EF005455)

50 Hz

Connectable conductor cross section solid-core (EF007337)

2.5 mm<sup>2</sup>

Ambient temperature during operating (EF007515)

-5 °C

Degree of protection (IP) (EF005474)

IP21

Leakage current type (EF002560)

Other

Voltage type (EF000187)

AC

Concurrently switching neutral conductor (EF005997)

Yes

Anti- nuisance tripping version (EF009497)

Yes

Rated short-circuit breaking capacity according to IEC 60947-2 (EF006065)

3 kA

Rated short-circuit breaking capacity according to EN 61009 (EF012628)

3 kA

Rated short-circuit breaking capacity I<sub>cn</sub> according to EN 61009-1 (EF011981)

3 kA

Rated fault current (EF002358)

0.03 A

Number of protected poles (EF005548)....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 077532 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.