

INDUSTRIAL COMPONENT DATA

077533 LEGRAND MO-INTER DIF 10A 10MA 2M BL

Brand: LEGRAND | Manufacturer Part Number: 077533



Manufacturer	LEGRAND
MPN / Reference	077533
Catalog number	077533
Category	Earth leakage circuit breaker
Minimum order	1 Pcs
Document ID	EO-B485636E62
Generated	2026-07-29

Product Overview

MO-INTER DIF 10A 10MA 2M BL

RCBO Mosaic - 1 pole - with N 230 V~ and test button - 10 A - 10 mA - 2 modules -white

Mosaic differential circuit breaker - 1P+N - 10A - 10mA- 2mod - White

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > MOSAIC, ARTEOR AND CELIANE MECHANISMS

Additional Product Information

Pack (number of units)1

Volume (dm3)0.188

Weight (g)87.00

Product characteristicsProximity MCBs

Used for local protection of part of a circuit against overloads and short circuits

Used in addition to the main protection device

Due to its proximity to the user and its discrimination with the main protection device, the restart can be immediate
2 modules

Single pole RCBOs + Neutral 230 V~

Provides additional protection of people (premises with conductive flooring, presence of water, etc.) against direct contact
with live parts or earth leakages

White

10 A - 10 mA with test button

General characteristicsMosaic™ Programme mechanisms - voltage surge protector, replacement module, buzzers, bells,

blanking plates, cable outlets and proximity MCBs

ETIM for 077533 Circuit breakers and fuses (EC000905)

Feature Name

Feature Value

Frequency (EF005455)

50 Hz

Connectable conductor cross section solid-core (EF007337)

2.5 mm²

Ambient temperature during operating (EF007515)

-5 °C

Degree of protection (IP) (EF005474)

IP21

Leakage current type (EF002560)

Other

Voltage type (EF000187)

AC

Concurrently switching neutral conductor (EF005997)

Yes

Anti- nuisance tripping version (EF009497)

Yes

Rated short-circuit breaking capacity according to IEC 60947-2 (EF006065)

3 kA

Rated short-circuit breaking capacity according to EN 61009 (EF012628)

3 kA

Rated short-circuit breaking capacity I_{cn} according to EN 61009-1 (EF011981)

3 kA

Rated fault current (EF002358)

0.01 A

Number of protected poles (EF005548)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 077533 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.