

INDUSTRIAL COMPONENT DATA

077646L LEGRAND KIT 4 CHARG SS FIL 15W ALU EU

Brand: LEGRAND | Manufacturer Part Number: 077646L



Manufacturer	LEGRAND
MPN / Reference	077646L
Catalog number	077646L
Category	USB power supply
Minimum order	1 Pcs
Document ID	EO-BCBFBC2621
Generated	2026-08-02

Product Overview

KIT 4 CHARG SS FIL 15W ALU EU

Kit with 4 15W chargers for integration into 80mm furniture. 1 100W power supply (plug-in). 4 RJ45 cables 1m. 2P plug (European).

Kit with 4 15W wireless chargers to embed European plug - Aluminum

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > MOSAIC, ARTEOR AND CELIANE MECHANISMS

Additional Product Information

Overview

Disq80 Qi 4 15W wireless chargers for 80mm furniture. Qi technology. Antiskid. IK08 IP44. 100W 240V power supply, 2.5m cable, 4 RJ45 (1m), 2P plug (eu), 8 adhesive bases, 4 identifications. LED. Halogen-free. Black description

Kit 4 chargers for furniture delivered with: power ref. 077639L (110-240 V~ - 100 W) equipped with a cable (2.50 m) and a 2P European plug, 4 RJ45 cables (1.0 m), (compatible with RJ45 cable. Cat 5 or Cat. 6 length from 0.5 to 10 m), 8 adhesive bases + 8 cable ties and 4 identification stickers for use in public spaces. Chargers equipped with an RJ45 input and an output for star or series connection. It can be used to fully charge a smartphone equipped with an induction receiver.

Designed for horizontal mounting on furniture. Suitable for use in passageways or transit areas, offices, kitchen countertops.

It does not interfere with other wireless transmissions (Zigbee, TNT, GSM, 4G, etc). Wireless charger equipped with an 8 cm2 induction antenna for quick pairing with the smartphone. Non-slip coated surface to securely hold the terminal during charging.

specifications

Model Other

Operating voltage 48-48 V
Connection Method Other
Type of mounting Recessed mounted (plaster)
Colour aluminium
Device width 87 mm
Device height 87 mm
Device Depth 27 mm
Min. depth of the recessed box 0 mm
Suitable for protection grade (IP) IP44
Impact resistance IK08
Antibacterial treatment No
Wireless Yes
Installation Depth 24.5 mm
Operating Temperature 5-45°C
Storage....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 077646L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.