

INDUSTRIAL COMPONENT DATA**077651L LEGRAND MO-USB TO 1M 15W AL**

Brand: LEGRAND | Manufacturer Part Number: 077651L

PRODUCT IMAGE\n\nNOT
AVAILABLE

Manufacturer	LEGRAND
MPN / Reference	077651L
Catalog number	077651L
Category	USB power supply
Minimum order	1 Pcs
Document ID	EO-0BAB2043E7
Generated	2026-08-03

Product Overview

MO-USB TO 1M 15W AL

USB charger base 1 single port module Type A - 3A - 15W - Aluminum

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **LEGRAND > MOSAIC, ARTEOR AND CELIANE MECHANISMS****Additional Product Information**

1 USB Type A charger base with 1 module. 3A, 15W. For optimal charging of portable devices such as phones, smartphones, MP3 or MP4, speakers, watches, game consoles, powerbanks. 1 module: compact format to save space. Standby consumption 0.1 W. Aluminum color. Indoor use. For installation in floor boxes, columns, mini-columns, workstations and DLP ducts. Not compatible with Batibox recessed boxes. Dimension 45x22.5x41mm. IK04 IP40. Polycarbonate material. Model Other

Number of USB-A ports 1

Number of USB-C ports 0

Operating voltage 100-240 V

frequency 50-60 Hz

Maximum output current 3000 mA

Output voltage 5-5 V

Power consumption 0.069 W

Connection Method Screw-on terminal

Type of mounting Recessed mounted (plaster)

Colour aluminium

RAL number 7040
Device width 22.5 mm
Device height 45 mm
Device Depth 41 mm
Min. depth of the recessed box 40 mm
Suitable for protection grade (IP) IP40
Impact resistance IK04
Antibacterial treatment No
Wireless No
Installation Depth 32.5 mm
Operating Temperature 5-40 °C
Storage temperature -20-70 °C
Type of voltage AC
Power Delivery No
USB Power Output 15
Nominal current 0.5-0.5 A
Neutral Mandatory Yes
Display of markings on the connection terminals Yes
Compliant with commissioning tests (1000 V) No
Halogen-free Yes
Number of terminals 2
Terminal capacity 1.5-2.5 mm²
Connection Cable Type Flexible or rigid
Core cross-section 1.5-2.5 mm²
ETIM for 077651L Domestic wiring accessories and controls (EC002949)
Feature Name
Feature Value
Model (EF000010)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 077651L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.