

INDUSTRIAL COMPONENT DATA

077652L LEGRAND CHARG 1M 1USB TO 15W NOIR

Brand: LEGRAND | Manufacturer Part Number: 077652L



Manufacturer	LEGRAND
MPN / Reference	077652L
Catalog number	077652L
Category	USB power supply
Minimum order	1 Pcs
Document ID	EO-CDE6CACB6A
Generated	2026-08-04

Product Overview

CHARG 1M 1USB TO 15W NOIR

USB charger base 1 single port module type A - 3A - 15W - Matte black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LEGRAND > MOSAIC, ARTEOR AND CELIANE MECHANISMS

Additional Product Information

specifications

Model Other

Number of USB-A ports 1

Number of USB-C ports 0

Operating voltage 100-240 V

frequency 50-60 Hz

Maximum output current 3000 mA

Output voltage 5-5 V

Power consumption 0.069 W

Connection Method Screw-on terminal

Type of mounting Recessed mounted (plaster)

Colour Black

RAL number 7015

Device width 22.5 mm

Device height 45 mm

Device Depth 41 mm
Min. depth of the recessed box 40 mm
Suitable for protection grade (IP) IP40
Impact resistance IK04
Antibacterial treatment No
Wireless No
Installation Depth 32.5 mm
Operating Temperature 5-40 °C
Storage temperature -20-70 °C
Type of voltage AC
Nominal Voltage 100-240 V
Power Delivery No
Nominal current 0.5-0.5 A
Neutral Mandatory Yes
Display of markings on the connection terminals Yes
Compliant with commissioning tests (1000 V) No
Halogen-free Yes
Number of terminals 2
Terminal capacity 1.5-2.5 mm²
Connection Cable Type Flexible or rigid
Core cross-section 1.5-2.5 mm²
ETIM for 077652L Domestic wiring accessories and controls (EC002949)
Feature Name
Feature Value
Model (EF000010)
Other
Mounting method (EF000003)
Flush mounted
Suitable for degree of protection (IP) (EF006755)
IP40
Connection type (EF000124)
Screwed terminal
Operating voltage (EF003983)
100 V
Device depth (EF008810)
41 mm
Impact strength (EF004293)
IK04
Anti-bacterial treatment (EF023790)
No
Number of ports USB-C (EF017049)
0
Min. depth of built-in installation box (EF012278)
40 mm
Output voltage (EF003933)
5 V
Power consumption (EF000346)

0.069 W....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 077652L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.