

## INDUSTRIAL COMPONENT DATA

## 077672L LEGRAND MO-2USB A+C 1M 15W NM

Brand: LEGRAND | Manufacturer Part Number: 077672L



|                 |                  |
|-----------------|------------------|
| Manufacturer    | LEGRAND          |
| MPN / Reference | 077672L          |
| Catalog number  | 077672L          |
| Category        | USB power supply |
| Minimum order   | 1 Pcs            |
| Document ID     | EO-7396C69464    |
| Generated       | 2026-08-01       |

## Product Overview

MO-2USB A+C 1M 15W NM

USB charger base 1 module two ports Type A+C - 3A 15W - Matte black

1mod USB charger base two ports Type A+C - 3A 15W - Matte black

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path LEGRAND &gt; MOSAIC, ARTEOR AND CELIANE MECHANISMS

## Additional Product Information

2 USB type A+C charger bases with 1 module. 3A, 15W. For optimal charging of portable devices such as phones, smartphones, MP3 or MP4, speakers, watches, game consoles, powerbanks. 1 module: compact format to save space.

Matte black color. Standby consumption 0.1 W. Indoor use. For installation in floor boxes, columns, mini-columns, workstations and DLP ducts. Not compatible with Batibox recessed boxes. Dimension 45x22.5x41mm. IK04 IP40.

Polycarbonate material. Model Other

Number of USB-A ports 1

Number of USB-C ports 1

Operating voltage 100-240 V

frequency 50-60 Hz

Maximum output current 3000 mA

Output voltage 5-5 V

Power consumption 0.091 W

Connection Method Screw-on terminal

Type of mounting Recessed mounted (plaster)

Colour Black  
RAL number 7015  
Device width 22.5 mm  
Device height 45 mm  
Device Depth 41 mm  
Min. depth of the recessed box 40 mm  
Suitable for protection grade (IP) IP40  
Impact resistance IK04  
Antibacterial treatment No  
Wireless No  
Installation Depth 32.5 mm  
Operating Temperature 5-40 °C  
Storage temperature -20-70 °C  
Type of voltage AC  
Power Delivery No  
USB Power Output 15  
Nominal current 0.5-0.5 A  
Neutral Mandatory Yes  
Display of markings on the connection terminals Yes  
Compliant with commissioning tests (1000 V) No  
Halogen-free Yes  
Number of terminals 2  
Terminal capacity 1.5-2.5 mm<sup>2</sup>  
Connection Cable Type Flexible or rigid  
Core cross-section 1.5-2.5 mm<sup>2</sup>  
ETIM for 077672L Domestic wiring accessories and controls (EC002949)  
Feature Name  
Feature Value  
Model (EF00001...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LEGRAND / 077672L with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.